


2021 GENERAL
CATALOGUE
Instruments for Water Analysis

 milwaukee

COMMITTED TO TOTAL CUSTOMER SATISFACTION

Milwaukee is a dynamic worldwide manufacturer of electrochemical Instrumentation for water analysis to measure pH, Redox, Conductivity, Salinity, Dissolved Oxygen, Temperature, Turbidity, Chlorine, Ammonia, Copper, Chloride, Phosphate, Iron, etc.

Milwaukee serves all markets where water quality measurements are required: Laboratory market, food and beverage, environmental, education and government, water and waste water treatment, pharmaceutical and biotechnology, chemical, agriculture and horticulture, hydroponics, aquariums, swimming pools, etc.

Thanks to your valuable feedback our R&D team has designed a new line of instruments for laboratory and field measurements.

Many of our instruments combine 2 or more parameters providing added versatility and excellent value for money. With an extended range of products, from basic hand held instruments to high performance laboratory bench meters, Milwaukee products have a reputation for reliability and accuracy.

All of our instruments are supplied with probes, electrode holders, buffer solutions and many come in a hard carrying case and ready for use.

Milwaukee Instruments are available worldwide through a selected network of distributors and associated companies that are committed to Total Customer Satisfaction.

Everyone in Milwaukee Instruments is committed to exceeding your expectations.



Global Offices



**Europe, South America, Africa,
Asia, Middle East and Pacific Rim**

Milwaukee Electronics Kft.

Alsó-Kikötő sor 11.C
H-6726 Szeged - HUNGARY
tel: +36 62 428 050
fax: +36 62 428 051
e-mail: sales@milwaukeeinst.com

























United States of America

Milwaukee Instruments, Inc.

2950 Business Park Drive
Rocky Mount - NC 27804 - U.S.A.
tel: +1 252 443 3630
fax: +1 252 443 1937
e-mail: sales@milwaukeetesters.com

Beauty of

Symbols

	CE CE Certified products
	IP65 IP65 rated housing
	IP67 IP67 rated housing
	GLP (Good Laboratory Practices) Good Laboratory Practices requires that time and date should be recorded with the parameters measured
	USB Port Communication via opto-isolated USB port
	2 Years Warranty Instruments are covered by 2 years warranty
	3 Years Warranty Instruments are covered by 3 years warranty
	7 pH Memorized buffers 7 pH Memorized buffers for calibration
	MEM MEM key allows to memorize the last measurement
	LOG LOG key allows to save up to 1000 measurements
	ALARM A LED light warns the user in the event the reading is outside the set point
	2 Point Calibration Calibration can be performed at 1 or 2 points
	3 Point Calibration Calibration can be performed at 1, 2 or 3 points
	5 Point Calibration Calibration can be performed at 3 or 5 points
	Multiparameter instruments Instruments that measure more than 1 parameter
	Automatic Temperature Compensation Automatically corrects the measured value based on the temperature of the solution
	Manual Temperature Compensation Is a method for temperature compensation through the manual input of sample temperature value
	Auto-Buffer Auto-Buffer Recognition ensures that correct buffer values are used during calibration
	Dual Level Display Displays simultaneously 2 parameters
	Replaceable Electrode Instrument with replaceable electrode
	Self-diagnostics Messages Messages on the LCD to make the calibration easy and accurate
	LED The lightsource is the LED with different wavelengths

Contents

Highlights	2
New Meters	3
New Bench Meters	4
pH/ORP/Temp Measurements	
pH/ORP/Temp Bench Meters	6
pH Electrodes	
pH Electrodes basic	8
pH/ORP/Temp Measurements	
pH/ORP/Temp Portable Meters (Professional)	12
Budget pH/ORP/Temp Portable Meters	14
pH Measurements in Soil	15
pH Measurements in Cheese	16
pH/Temp Pocket Testers (Professional)	17
pH/ORP/Temp Pocket Testers (Professional)	18
pH Testers	19
pH Monitors	20
pH/ORP Controllers	21
Peristaltic Dosing Pumps	22
Conductivity/TDS/NaCl/Temp Measurements	
EC/TDS/NaCl/Temp Bench Meter	23
EC/TDS/NaCl/Temp Portable Meter (Professional)	24
Budget EC/TDS Portable Meters	25
EC/TDS/Temp Pocket Testers (Professional)	26
EC/TDS Testers	27
EC/TDS Monitors	28
New EC Meters (MC311, EC40)	29
Dissolved Oxygen/Temp Measurements	
DO/Temp Bench Meter	30
Multiparameter Measurements	
Budget pH/EC/TDS Portable Meters	31
pH/EC/TDS/Temp Pocket Testers (Professional)	32
Light Measurements	
LUX Portable Meter	33
Colorimetric Measurements	
Free, Total Chlorine & pH Portable Photometer	34
Ammonia, Iron & Phosphate Portable Photometers	35
Free, Total Chlorine & Chloride Portable Photometers	36
Handy Photometers: Free & Total Chlorine	37
Handy Photometers: Phosphate, Iodine, Iron	38
Peroxide Value Photometer	39
Turbidity Measurements	
Turbidity Portable Meter	40
Refractometers	
Digital Refractometers for Brix, Fructose, Glucose and Invert Sugar	41
Digital Refractometers for Wine and Grape Product Measurements	42
Digital Refractometer for Sodium Chloride Measurements	43
Salt in Cheese Measurements	44
Digital Refractometer for Seawater Measurements	45
Digital Refractometer for Ethylene Glycol Measurements	46
Thermometers & NPK Test Kit	47
Mini-Titrators	48
pH Measurement in Meat	49
Electrodes & Probes	50
Electrode selection guide	51
Calibration, Maintenance & Cleaning Solutions	52
Warranty	53

Simplicity

Highlights in this Catalogue



The new innovative line of Milwaukee bench meters includes a lot of new features:

- pH extended range: -2.00 to 20.00 pH, -2.000 to 20.000 pH
- Rechargeable battery with 8 hrs battery life
- 2 USB ports: Standard USB socket to export data directly to a flash drive and micro USB to connect a computer for file export
- Data logging: 1000 logs can be stored in the built-in memory including readings, GLP data, date and time
- Different logging methods: manual log-on-demand (max. 200 logs); manual log-on-stability (max. 200 logs) and interval log (max. 600 samples; 100 lots)
- Electrode diagnostics feature checks and displays the condition of the pH electrode
- 5 points calibration (MW151)

The new innovative line of Milwaukee portable meters includes a lot of New features:

- IP67 waterproof casing
- pH extended range: -2.00 to 20.00 pH, -2.000 to 20.000 pH (MW106)
- Up to 5-point calibration with 7 standard calibration buffers and two custom buffers
- Micro USB to connect a computer for file export
- Data logging: 1000 logs can be stored in the built-in memory including readings, GLP data, date and time
- Different logging methods: manual log-on-demand (max. 200 logs); manual log-on-stability (max. 200 logs) and interval log (max. 600 samples; 100 lots)
- Electrode diagnostics feature checks and displays the condition of the pH electrode



MA871: Digital Brix Refractometer

The **MA871** is an optical instrument that employs the measurement of refractive index to determine the % Brix of sugar in aqueous solutions. The method is both simple and quick. Samples are measured after a simple user calibration with deionized or distilled water. Within seconds the instrument measures the refractive index of the sample and converts it to % Brix concentration units.

Measuring pH in cheese

Using **MW101 PRO** pH portable meter with a **MA920B/1** pH electrode for measuring pH in cheese. During the cheese making process, the pH is measured multiple times. Each type of cheese may have a slightly different process and pH level. It is important for manufacturers and companies to be aware of the differences and treat each cheese variety with the quality and care it deserves. Measuring the pH of cheese essentially gives the manufacturer control of the cheese process.



COMING SOON

Dissolved oxygen and temperature portable meter

MW605 MAX is a portable, IP67 rated meter designed for fresh and saltwater measurements of dissolved oxygen (DO).

The MW605 meter is compatible with MA860 galvanic DO probe. Galvanic probes require no conditioning and thus the instrument is ready to measure when it is powered on. Concentration measurements are automatically compensated for temperature and salinity. Temperature is automatically measured (in both degree Celsius and Fahrenheit) and compensated. Salinity and altitude can be configured in Setup.

Other features include:

- IP67 waterproof casing
- Auto-off feature to prolong battery life
- One or two % saturation calibration points at 100% (water saturated air) and 0% (zero oxygen solution)
- Dedicated GLP key to store and recall data on system status
- Available log space for up to 1000 records
- Logged data can be exported using a USB cable



pH/ORP/EC/TDS/NaCl/Temp bench meter

MW180 MAX is a compact and versatile bench meter with a user-friendly interface that can measure six different parameters – pH, ORP, EC, TDS (Total Dissolved Solids), percentage of salinity (NaCl%) and temperature – when paired with the respective probe.

pH calibration can be performed in up to 5-point (selectable between 7 standard calibration buffers and two custom buffers), to improve measurement reliability even when testing samples with wide differences in pH.

The auto-ranging feature for both EC and TDS measurements automatically sets the most suitable resolution for the tested sample. All measurements can be automatically (ATC) or manually temperature compensated (MTC) with a user-selectable compensation coefficient. The temperature compensation can be disabled if the actual conductivity value is required (No TC).

MW180 has GLP data review and the data can be transferred to a PC through a USB port.

A unique device identity code protects against the risks of loss and misuse.

Dissolved oxygen and temperature bench meter

MW190 MAX is a compact and versatile bench meter designed for testing dissolved oxygen in the pharmaceutical and food industry, as well as monitoring in water treatment plants.

Concentration measurements are automatically compensated for temperature and salinity. Salinity and altitude can be configured in Setup. Temperature is automatically measured (in both degree Celsius and Fahrenheit) and compensated.

Other features include:

- Easy to read LCD display
- Built-in rechargeable battery with an 8-hour capacity
- Auto-off feature to prolong battery life
- Battery charger with battery monitor
- Internal clock and date to keep track of different time-dependent functions (calibration timestamp, calibration time out)
- Measurement logging (on demand, on stability, interval)
- Available log space for up to 1000 records
- Logged data can be exported using a USB cable or directly on a USB flash drive
- Dedicated GLP key to store and recall data on system status
- For accurate measurements, use the electrode holder supplied with the bench meter.



**Looking for research grade
Look no further than Milwaukee. Our
top meters provide an affordable solution for
pH • ORP • EC •**



instruments on a budget?

Our new high performance Bench- solution to your measuring needs. TDS • Temp • DO

MW150 MAX: pH/ORP/Temp bench meter

MW151 MAX: pH/ORP/Temp bench meter with logging

MW160 MAX: pH/ORP/ISE/Temp bench meter with logging (coming soon)

MW170 MAX: Autoranging EC/TDS/NaCl/Temperature laboratory bench meter

MW180 MAX: pH/ORP/EC/TDS/NaCl/Temperature combination bench meter

MW190 MAX: Extended range dissolved oxygen meter

Key features:

Built in rechargeable battery with 8 hours battery life supplied complete with battery charger, sensors, calibration solutions, electrode holder ready for use.



Data logging: 1000 logs can be stored in the built-in memory including readings, GLP data, date and time.


Different logging methods: manual log-on-demand (max. 200 logs); manual log-on-stability (max. 200 logs) and interval log (max. 600 samples; 100 lots).

Electrode diagnostics feature checks and displays the condition of the pH electrode



2 USB ports: Standard USB socket to export data directly to a flash drive and micro USB to connect a computer for file export

Custom dual level LCD: Large and easy-to-read Custom dual level LCD with simultaneous readings and with user-friendly icons.



The complete Milwaukee sensor portfolio covers the whole scope of pH applications. These range from routine measurements to specific applications. To find your perfect match, go to page 51 – Electrode Selection Guide.

MW150 MAX

pH/ORP/Temperature Laboratory Bench Meter

- 3 Year warranty
- MEM
- ATC
- MTL
- 3 Points
- Dual Display
- Self diagnosis
- 7 Menus
- CE
- GLP



MW150 MAX is an advanced pH/ORP/Temp microprocessor-based bench meter. It is ideal for students and technicians who need fast and reliable measurements.

This meter is provided with a series of new diagnostic features which add an entirely new dimension to the measurement of pH, by allowing the user to dramatically improve the reliability of the measurement:

- Up to 3-point automatic calibration with 7 standard calibration buffers
- Automatic or manual temperature compensation
- Built-in rechargeable battery with 8 hours battery life
- Auto-off feature to preserve battery energy
- Battery charger with battery monitor
- Dedicated GLP key
- Alphanumeric LCD displayed messages for user friendly, intuitive information/warning/error messages
- Internal clock and date to keep track of different time-dependent functions (calibration, timestamp, calibration time out)
- dedicated GLP key

Glass Electrode & Temperature Probe

Choose from our wide selection of pH and ORP electrodes at pages 8 and 50.



Custom dual level LCD

Large and easy-to-read Custom dual level LCD with simultaneous readings and with user-friendly icons.



Specifications		MW150 MAX
Range	pH mV Temp	-2.00 to 20.00 pH ±1000.0 mV / ±2000.0 mV -20.0 to 120.0°C / -4.0 to 248.0°F
Resolution	pH mV Temp	0.01 pH 0.1 mV / 0.1 mV 0.1°C / 0.1°F
Accuracy (@25°C / 77°F)	pH mV Temp	±0.01 pH ±0.2 mV / ±1 mV ±0.4°C / ±0.8°F
pH Calibration		up to 3-point automatic pH calibration, 7 standard calibration buffers (pH 1.68, 4.01, 6.86, 7.01, 9.18, 10.01 and 12.45)
Temperature Compensation		automatic from -20.0 to 120.0°C / -4.0 to 248.0°F or manual, without temperature probe
pH Electrode		MA917B/1 (included)
Temperature Probe		MA831R (included)
Power Supply		12 VDC adapter (included)
Battery life		8 hours
Auto-off		5, 10, 30, 60 minutes or off
Environment		0 to 50 °C; max RH 95%
Packaging dimensions		335 x 120 x 255 mm
Packaging weight		2 kg

Accessories

- | | |
|--|---|
| MA9001 pH 1.68 buffer solution, 230 mL bottle | MA9016 Electrode cleaning solution, 230 mL bottle |
| MA9004 pH 4.01 buffer solution, 230 mL bottle | MA9112 pH 12.45 buffer solution, 230 mL bottle |
| MA9006 pH 6.86 buffer solution, 230 mL bottle | MA9310 12 VDC Adapter, 220 V |
| MA9007 pH 7.01 buffer solution, 230 mL bottle | MA9311 12 VDC Adapter, 110 V |
| MA9009 pH 9.18 buffer solution, 230 mL bottle | MA9315 Electrode Holder |
| MA9010 pH 10.01 buffer solution, 230 mL bottle | MA917B/1 Glass body, double junction refillable pH electrode |
| MA9011 Refilling Electrolyte Solution 3.5M KCl for pH/ORP electrodes, 230 mL | MA831R Temperature probe |
| MA9012 Refilling Electrolyte Solution 1M KNO ₃ , 230 mL, food applications | |
| MA9015 Electrode storage solution, 230 mL bottle | |



Ordering Information

- MW150 MAX** is supplied complete with:
- **MA917B/1** Double junction refillable pH electrode
 - **MA831R** Temperature Probe
 - **MA9315** Electrode Holder
 - **M10004** pH 4.01 Sachet Buffer Solution
 - **M10007** pH 7.01 Sachet Buffer Solution
 - **M10010** pH 10.01 Sachet Buffer Solution
 - **M10016** Sachet Electrode Cleaning Solution
 - **MA9310** 12 VDC Adapter
 - Graduated pipette
 - Instruction manual

MW151 MAX

pH/ORP/Temperature Logging Laboratory Bench Meter

This high performance microprocessor-based pH/ORP/Temp Bench meter is an ideal tool in schools, laboratories and production plants. It is provided with a series of new diagnostic features which add an entirely new dimension to the measurement of pH, by allowing the user to dramatically improve the reliability of the measurement:

- Up to 5-point calibration with 7 standard calibration buffers and two custom buffers
- 2 USB ports: Standard USB socket to export data directly to a flash drive and micro USB to connect a computer for file export
- Data logging: 1000 logs can be stored in the built-in memory including readings, GLP data, date and time
- Different logging methods: manual log-on-demand (max. 200 logs); manual log-on-stability (max. 200 logs) and interval log (max. 600 samples; 100 lots)
- Electrode diagnostics feature checks and displays the condition of the pH electrode
- Built-in rechargeable battery with 8 hours battery life
- Battery charger with battery monitor
- Dedicated GLP key
- Alphanumeric LCD displayed messages for user friendly, intuitive information/warning/error messages



- 3 Years warranty
- LOG
- ATC
- MTU
- 5 Points
- Low Display
- Self diagnostics
- 7 Memorable buffers
- CE
- USB
- GLP

Specifications	MW151 MAX
Range	pH -2.00 to 20.00 pH / -2.000 to 20.000 pH mV ±1000.0 mV / ±2000.0 mV Temp -20.0 to 120.0°C / -4.0 to 248.0°F
Resolution	pH 0.01 pH / 0.001 pH mV 0.1 mV / 0.1 mV Temp 0.1°C / 0.1°F
Accuracy (@20°C)	pH ±0.01 pH / ±0.002 pH mV ±0.2 mV / ±1 mV Temp ±0.4°C / ±0.8°F
pH Calibration	up to 5-point automatic pH calibration, 7 standard calibration buffers (pH 1.68, 4.01, 6.86, 7.01, 9.18, 10.01 and 12.45) and two custom buffers
Temperature Compensation	automatic from -20.0 to 120.0°C / -4.0 to 248.0°F or manual, without temperature probe
pH Electrode	MA917B/1 (included)
Temperature Probe	MA831R (included)
Log	Maximum 1000 records; On demand, 200 samples; On stability, 200 samples Interval logging, 600 samples (max. 100 lots)
PC connectivity	1 USB port, 1 micro USB port
Power Supply	12 VDC adapter (included), 5 VDC USB adapter
Battery life	8 hours
Auto-off	5, 10, 30, 60 minutes or off
Environment	0 to 50 °C; max RH 95%
Packaging dimensions	335 x 120 x 255 mm
Packaging weight	2 kg



Glass Electrode & Temperature Probe

Choose from our wide selection of pH and ORP electrodes at pages 8 and 50.

Innovative Design

Compact-size ergonomic design with electrode holder that can hold multiple electrodes & probes.



Accessories

- MA9001 pH 1.68 buffer solution, 230 mL bottle
- MA9004 pH 4.01 buffer solution, 230 mL bottle
- MA9006 pH 6.86 buffer solution, 230 mL bottle
- MA9007 pH 7.01 buffer solution, 230 mL bottle
- MA9009 pH 9.18 buffer solution, 230 mL bottle
- MA9010 pH 10.01 buffer solution, 230 mL bottle
- MA9011 Refilling Electrolyte Solution 3.5M KCl for pH/ORP electrodes, 230 mL
- MA9012 Refilling Electrolyte Solution 1M KNO3, 230 mL, food applications
- MA9015 Electrode storage solution, 230 mL
- MA9016 Electrode cleaning solution, 230 mL
- MA831R Temperature probe



- MA9112 pH 12.45 buffer solution, 230 mL bottle
- MA9310 12 VDC Adapter, 220 V
- MA9311 12 VDC Adapter, 110 V
- MA9315 Electrode Holder
- MA917B/1 Glass body, double junction refillable pH electrode
- MA924B/1 ±2000 mV Glass ORP electrode, refillable with BNC connector and 1 meter cable
- SE300 Platinum ORP electrode with 1 m cable

Ordering Information

- MW151 MAX is supplied complete with:
- MA917B/1 Double junction refillable pH electrode
 - MA831R Temperature Probe
 - MA9315 Electrode Holder
 - M10004 pH 4.01 Sachet Buffer Solution
 - M10007 pH 7.01 Sachet Buffer Solution
 - M10010 pH 10.01 Sachet Buffer Solution
 - M10016 Sachet Electrode Cleaning Solution
 - MA9310 12 VDC Adapter
 - Graduated pipette
 - USB cable
 - Instruction manual




pH electrodes are constructed from a special composition glass which senses the hydrogen ion concentration. This glass is typically composed of alkali metal ions. The alkali metal ions of the glass and the hydrogen ions in solution undergo an ion exchange reaction, generating a potential difference. In a combination pH electrode, the most widely used variety, there are actually two electrodes in one body. One portion is called the measuring electrode, the other the reference electrode. The potential generated at the junction site of the measuring portion is due to the free hydrogen ions present in solution.

The potential of the reference portion is produced by the internal element in contact with the reference fill solution. This potential is always constant. In summary, the measuring electrode delivers a varying voltage and the reference electrode delivers a constant voltage to the meter. The voltage signal produced by the pH electrode is a very small, high impedance signal. The input impedance requires to be interfaced only with equipment with high impedance circuits.

Milwaukee has a wide assortment of pH and ORP electrodes to meet all your specific requirements. Finding the right electrode for a specific application is a very important task and in order to solve this selection problem it is important to consider the following:

- Glass body electrode versus Epoxy (plastic) body electrode:** Glass body electrodes stand higher temperatures (typically 100°C against 80°C for plastic) and are more resistant to corrosive chemicals and solvents. They are easier to clean and are available in different shapes depending on the application. On the other hand plastic body electrodes are more rugged and the glass bulb is better protected.
- Gel filled electrodes versus refillable electrodes:** refillable electrodes last longer since electrolyte can be changed for repeated usage. The response is faster due to a greater outflow of electrolyte into the sample and therefore less likely to clog. Gel filled electrodes require less maintenance and resist to higher pressure.
- Double reference junction versus Single junction reference:** Double junction reference electrodes have a longer life and protects the sample measured from silver contamination from the electrolyte. The Silver wire is more protected and therefore gets less contaminated. The single junction electrodes normally cost less and are ideal for general purpose applications
- Conic shaped versus Sphere shaped:** The conic-shaped electrode is easier to clean and to maintain (ideal for applications such as dairy). Has a more rugged tip and therefore ideal for penetration. The sphere-shaped has a faster response time due to the larger surface area on the bulb.



Model	MA919B/1	MA924B/1
Measuring Range	0 to 13 pH	±2000 mV
Temperature Range	-5 to 70 °C	0 to 70 °C
Shaft material	glass	glass
Reference Electrolyte	KCL 3.5M	KCL 3.5M
Reference Junction	open	open
Reference Type	double Ag/AgCl	double Ag/AgCl
Shape of membrane	spheric	Platinum ring
Max. Pressure	0,1 bar	0,1 bar
Connector type	BNC	BNC
Cable length	coaxial 1 meter	coaxial 1 meter
Shaft length	120 mm	120 mm
Diameter	8 mm	8 mm
Application	food laboratory	food laboratory

pH Electrode basics

The pH electrode, due to the nature of its construction, needs to be kept moist at all times. In order to operate properly, glass needs to be hydrated. Hydration is required for the ion exchange process to occur. If an electrode should become dry, it is best to place it in some tap water for half an hour to condition the glass.

pH electrodes are like batteries; they run down with time and use. As an electrode ages, its glass changes resistance. This resistance change alters the electrode potential. For this reason, electrodes need to be calibrated on a regular basis. Calibration in pH buffer solution corrects for this change. Calibration of any pH equipment should always begin with buffer 7.0 as this is the "zero point." The pH scale has an equivalent mV scale. The mV scale ranges from +420 to -420 mV. At a pH of 7.0 the mV value is 0. Each pH change corresponds to a change of approx. ± 60 mV. As pH values become more acidic the mV values become greater.

pH electrodes have junctions which allow the internal electrolyte solution of the measuring electrode to leak out into the solution being measured.


Glass Conic Tip Sensor




Glass Spheric Sensor



Dome-shaped



Model	MA916B/1 - MA916B/3	MA917B/1	MA918B/1
Measuring Range	0 to 12 pH	0 to 14 pH	0 to 12 pH
Temperature Range	0 to 60°C	0 to 70°C	-5 to 60°C
Shaft Material	glass	glass	glass
Reference Electrolyte	KCl 3.5M	KCl 3.5M	KCl 3.5M
Reference Junction	ceramic, single	ceramic, single	ceramic, triple
Reference Type	double, Ag/AgCl	double, Ag/AgCl	double, Ag/AgCl
Shape of membrane	spheric	spheric	conic
Max pressure	0.1 bar	0.1 bar	0.1 bar
Connector Type	BNC	BNC	BNC
Cable length	coaxial, 1 or 3 m	coaxial, 1 m	coaxial, 1 m
Shaft length	120 mm	120 mm	120 mm
Diameter	12 mm	12 mm	12 mm
Application	laboratory applications	laboratory applications	food-laboratory applications




This junction can become clogged by particulates in the solution and can also facilitate poisoning by metal ions present in the solution. If a clogged junction is suspected it is best to soak the electrode in tap water to dissolve the material and clear the junction. When not in use it is best to store the electrode in either buffer 4.0 or buffer 7.0. Never store an electrode in distilled or deionized water as this will cause migration of the electrolyte solution from the electrode.

How long a pH electrode will last will depend on how it is cared for and the solutions it is used to measure. Typically, a gel-filled combination pH electrode will last six months to 1 year depending on the care and application.

How long an electrode will last is determined by how well the probe is maintained and the pH application. The harsher the system, the shorter the lifespan. For this reason it is always a good idea to have a back-up electrode on hand to avoid any system down time. Calibration is also an important part of electrode maintenance. This assures not only that the electrode is behaving properly but that the system is operating correctly.

Electrode Storage Bottle Cap: All our pH and ORP electrodes are supplied with a bottle storage cap which helps to keep the glass bulb always wet.



Model	MA920B/1	MA991B/1	MA905B/3	MA925B/3
Measuring Range	0 to 12 pH	0 to 13 pH	0 to 13 pH	±2000 mV
Temperature Range	-5 to 50°C	-5 to 70°C	-10 to 80°C	-5 to 100°C
Shaft Material	PVDF	glass	PVDF	PVDF
Reference Electrolyte	Viscolene	gel	polymer	polymer
Reference Junction	open	ceramic, single	double PTFE	PTFE
Reference Type	single, Ag/AgCl	single, Ag/AgCl	double Ag/AgCl	Ag/AgCl
Shape of membrane	conic	spheric	flat	flat Pt sensor
Max pressure	0.1 bar	0.1 bar	6 bar	6 bar
Connector Type	BNC	BNC	3/4" NPT - BNC	BNC
Cable length	coaxial, 1 m	coaxial, 1 m	3 m	3 meter
Shaft length	75 mm	120 mm	120 mm	135 mm
Diameter	6 mm	12 mm	22 mm	22 mm
Application	food-laboratory applications	laboratory applications	industrial applications	industrial applications

pH Electrode basics


Temperature compensation: When measuring pH using a pH electrode the temperature error from the electrode varies based on the Nernst Equation as 0.03 pH/10C/unit of pH away from pH7. The error due to temperature is a function of both temperature and the pH being measured. Temperature compensation can be achieved manually or automatically. Manual temperature compensation is usually achieved by entering the temperature of the fluid being measured into the instruments menu and then the instrument will display a "Temperature Compensated" pH reading.

This means that the temperature is corrected to the value expected at 25 °C. Automatic temperature compensation requires input from a temperature sensor and constantly sends a compensated pH signal to the display. Automatic temperature compensation is useful for measuring pH in systems with wide variations in temperature.

DIN Connector



BNC Connector



Model	MA913B/3 - B/5	MA923B/3 - B/5	SE-220	SE-300
Measuring Range	0 to 13 pH	±1999 mV	0 to 13 pH	±1999 mV
Temperature Range	20 to 60°C	20 to 60°C	-5 to 70 °C	20 to 60°C
Shaft Material	PEI	PEI	PEI	PEI
Reference Electrolyte	gel	gel	gel	gel
Reference Junction	ceramic, single	cloth	cloth	cloth
Reference Type	single, Ag/AgCl	single, Ag/AgCl	double Ag/AgCl	single, Ag/AgCl
Shape of membrane	spheric	spheric, platinum sensor	spheric	spheric, platinum sensor
Max pressure	2 bar	2 bar	2 bar	2 bar
Connector Type	BNC	BNC	BNC	BNC
Cable length	coaxial, 3 m or 5 m	7-pole, 3 m or 5 m	coaxial 1 meter	7-pole, 3 m or 5 m
Shaft length	120 mm	120 mm	120 mm	120 mm
Diameter	12 mm	12 mm	12 mm	12 mm
Application	drinking water, waste water	drinking water, waste water	drinking water, waste water	drinking water, waste water

MW105 MAX

Portable pH/ORP/Temp Meter



- 3 Years Warranty
- ATC
- 2 Points
- Dual Display
- Self-Diagnostics
- CE
- IP67
- GLP

The Milwaukee **MW105 MAX** meter combines all the features of a benchtop unit into a portable, IP67 rated meter. The instruments are provided with a series of new diagnostic features for improved pH measurement reliability:

- IP67 waterproof casing
- pH extended range: -2.00 to 20.00 pH
- up to 3-point automatic pH calibration, 7 standard calibration buffers (pH 1.68, 4.01, 6.86, 7.01, 9.18, 10.01 and 12.45)
- alphanumeric LCD displayed messages for user friendly, intuitive information / warning / error messages
- auto-off feature to preserve battery life
- internal clock and date to keep track of different time-dependent functions (calibration timestamp, calibration time out)
- dedicated GLP key

Hard Carrying Case

Each meter is supplied in a hard carrying case ideal for field measurements.



Specifications	MW105 MAX
Range	pH -2.00 to 20.00 pH mV ±2000 mV Temp* -20.0 to 120.0°C / -4.0 to 248.0°F
Resolution	pH 0.01 pH mV 1 mV Temp 0.1°C / 0.1°F
Accuracy (@25°C / 77°F)	pH ±0.02 pH mV ±1 mV Temp ±0.5°C up to 60°C; ±1°C outside / ±1°F up to 140°F; ±2°F outside
pH Calibration	automatic, up to 3 points calibration, 7 standard buffers available (1.68, 4.01, 6.86, 7.01, 9.18, 10.01, 12.45)
ORP calibration	factory calibrated
Temperature compensation	automatic, from -5 to 80 °C (-23 to 176 °F); manual
Probe	MA906BR/1 amplified pH/temperature probe (supplied)
Temperature probe	Built-in temperature probe
Input impedance	10 ¹² Ohm
Battery Type	3 x 1.5V alkaline AA (included)
Battery Life	Approx. 200 hours of use
Environment	0 to 50°C / 32 to 122°F; max RH 95%
Auto-off	5, 10, 30, 60 minutes or off
Packaging dimensions	305 x 280 x 115 mm
Packaging weight	1.22 kg

* Temperature range is limited to 80.0 °C, when using the MA906BR/1 probe

Calibration, Maintenance & Cleaning Solutions

Choose from our wide selection of calibration, maintenance and cleaning solutions at page 52.



Ordering Information

MW105 MAX is supplied complete with:

- **MA906BR/1** amplified pH/temperature probe
- **MA9315** electrode holder
- **M10004** pH 4.01 buffer solution (20 mL sachet)
- **M10007** pH 7.01 buffer solution (20 mL sachet)
- **M10010** pH 10.01 buffer solution (20 mL sachet)
- **M10016** electrode cleaning solution (20 mL sachet)
- Graduated pipette
- 1.5V alkaline AA battery (3 pcs.)
- Instrument quality certificate
- Instruction manual

Accessories

- MA906BR/1** amplified pH/temperature probe
- M10000B** Electrode rinse solution, 20 mL (25 pcs)
- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)

- M10010B** pH 10.01 buffer solution, 20 mL sachet (25 pcs)
- MA9004** pH 4.01 buffer solution, 230 mL bottle
- MA9006** pH 6.86 buffer solution, 230 mL bottle
- MA9007** pH 7.01 buffer solution, 230 mL bottle
- MA9009** pH 9.18 buffer solution, 230 mL bottle
- MA9010** pH 10.01 buffer solution, 230 mL bottle
- MA9015** Electrode storage solution, 230 mL
- MA9016** Electrode cleaning solution, 230 mL



MW106 MAX

Portable pH/ORP/Temp Meter

The Milwaukee **MW106 MAX** meter combines all the features of a benchtop unit into a portable, IP67 rated meter. The instruments are provided with a series of new diagnostic features for improved pH measurement reliability:

- IP67 waterproof casing
- pH extended range: -2.00 to 20.00 pH/ -2.000 to 20.000 pH
- up to 5-point automatic pH calibration, 7 standard calibration buffers (pH 1.68, 4.01, 6.86, 7.01, 9.18, 10.01 and 12.45) and two custom buffers
- available log space for up to 1000 records
- alphanumeric LCD displayed messages for user friendly, intuitive information / warning / error messages
- auto-off feature to preserve battery life
- internal clock and date to keep track of different time-dependent functions (calibration timestamp, calibration time out)
- dedicated GLP key

Calibration, Maintenance & Cleaning Solutions

See page 52.



- 3 Years warranty
- ATC
- Points 2
- Disp Display
- Self diagnostics
- CE
- IP67
- GLP
- USB
- LOG

Specifications	MW106 MAX
Range	pH -2.00 to 20.00 pH / -2.000 to 20.000 pH mV ±2000 mV Temp* -20.0 to 120.0 °C (-4.0 to 248.0 °F)
Resolution	pH 0.01 pH / 0.001 pH mV 0.1 mV Temp 0.1°C / 0.1°F
Accuracy (@25°C)	pH ±0.01 pH / ±0.002 pH mV ±1 mV Temp ±0.5°C up to 60°C; ±1°C outside / ±1°F up to 140°F; ±2°F outside
pH Calibration	automatic, up to 5 points calibration, 7 standard buffers available (1.68, 4.01, 6.86, 7.01, 9.18, 10.01, 12.45) and two custom buffers
ORP Calibration	factory calibrated
Temperature Compensation	automatic, from -5 to 80°C / 23 to 176°F
Probe	MA906BR/1 amplified pH/temperature probe (supplied)
Temperature probe	Built-in temperature probe
Input impedance	10 ¹² Ohm
Log	Max. 1000 log records (stored in up to 100 lots) On demand, 200 logs / On stability, 200 logs / Interval logging, 1000 logs
PC connectivity	1 micro USB port
Battery Type	3 x 1.5V alkaline AA (included)
Battery Life	approx. 200 hours of use
Auto-off	5, 10, 30, 60 minutes or off
Environment	0 to 50°C ; 95% RH
Packaging dimensions	305 x 280 x 115 mm
Packaging weight	1.22 kg

* Temperature range is limited to 80.0 °C, when using the MA906BR/1 probe

Hard Carrying Case

Each meter is supplied in a hard carrying case ideal for field measurements.



Accessories

- | | |
|--|---|
| MA906BR/1 amplified pH/temperature probe | M10010B pH 10.01 buffer solution 20 mL sachet (25 pcs) |
| M10000B Electrode rinse solution, 20 mL sachet (25 pcs) | MA9004 pH 4.01 buffer solution, 230 mL bottle |
| M10004B pH 4.01 buffer solution 20 mL sachet (25 pcs) | MA9007 pH 7.01 buffer solution, 230 mL bottle |
| M10007B pH 7.01 buffer solution 20 mL sachet (25 pcs) | MA9015 Electrode storage solution, 230 mL |
| | MA9016 Electrode cleaning solution, 230 mL |



Ordering Information

- MW106 MAX** is supplied complete with:
- **MA906BR/1** amplified pH/temperature probe
 - **MA9315** electrode holder
 - **M10004** pH 4.01 buffer solution (20 mL sachet)
 - **M10007** pH 7.01 buffer solution (20 mL sachet)
 - **M10010** pH 10.01 buffer solution (20 mL sachet)
 - **M10016** electrode cleaning solution (20 mL sachet)
 - Graduated pipette
 - 1.5V alkaline AA battery (3 pcs.)
 - USB cable
 - Instrument quality certificate
 - Instruction manual

MW100 PRO/MW101 PRO/MW102 PRO+/MW500 PRO

Budget pH/ORP/Temperature Portable Meters for fast and reliable results



MW100 PRO, MW101 PRO, MW102 PRO+ and MW500 PRO are compact microprocessor-based pH, ORP and Temperature Portable Meters. These handy and ergonomically designed portable meters are ideal for anyone working on a low budget and still requires fast and reliable measurements.

These portable meters are suitable for a wide range of applications, such as Educational, Agriculture and Horticulture, as well as water and environmental analysis. These easy and fast to calibrate portable meters have a small, ergonomic and light case design. Other features include large and easy to read LCD and long battery life.

All meters are supplied with pH or ORP electrodes and calibration solutions in a carton box.

- **MW100 PRO** performs pH measurements with a 0.1 pH resolution.
- **MW101 PRO** performs pH measurements with a 0.01 pH resolution and with manual temperature compensation.
- **MW102 PRO+** is a microprocessor based pH/Temperature meter with extended range (-2.00 to 16.00 pH), Automatic Temperature Compensation, automatic calibration in 2 points and ± 0.02 pH accuracy.
- **MW500 PRO** performs ORP measurements with a range of ± 1000 mV.

Specifications	 MW100 PRO pH Meter	 MW101 PRO pH Meter	 MW102 PRO+ pH/Temp Meter	 MW500 PRO ORP Meter
Range	pH/ORP Temp. 0.0 to 14.0 pH	0.00 to 14.00 pH	-2.00 to 16.00 pH -5 to 70°C	± 1000 mV
Resolution	pH/ORP Temp. 0.1 pH	0.01 pH	0.01 pH 0.1°C	1 mV
Accuracy (@25°C)	pH/ORP Temp. ± 0.2 pH	± 0.02 pH	± 0.02 pH $\pm 0.5^\circ\text{C}$	± 5 mV
Typical EMC Deviation	pH Temp.		± 0.02 pH $\pm 0.5^\circ\text{C}$	
Temperature Compensation	N.A.	manual, 0 to 50°C	automatic, 0 to 70°C	
Calibration	manual, 2-point through offset and slope trimmers	manual, 2-point through offset and slope trimmers	automatic at 1 or 2 points with memorized buffers (pH 4.01, 7.01, 10.01)	
pH Electrode	SE220 (included)	SE220 (included)	SE220 (included)	
ORP Electrode				SE300 (included)
Temperature Probe			MA830R (included)	
Environment	0 to 50°C, max RH 95%	0 to 50°C, max RH 95%	0 to 50°C, max RH 95%	0 to 50°C, max RH 95%
Battery Type	1 x 9V alkaline (included)	1 x 9V alkaline (included)	1 x 9V alkaline (included)	1 x 9V alkaline (included)
Battery Life	approx. 300 hours of use	approx. 300 hours of use	approx. 300 hours of use after 8 minutes of non-use	approx. 300 hours of use
Auto-off				
Packaging dimensions	212 x 145 x 67 mm	212 x 145 x 67 mm	212 x 145 x 67 mm	212 x 145 x 67 mm
Packaging weight	440 g	420 g	500 g	400 g

Accessories

- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution 20 mL sachet (25 pcs)
- MA9004** pH 4.01 buffer solution, 230 mL bottle
- MA9007** pH 7.01 buffer solution, 230 mL bottle

- MA9010** pH 10.01 buffer solution, 230 mL
- MA9015** Electrode storage solution, 230 mL
- MA9016** Electrode cleaning solution, 230 mL
- MA830R** Temperature probe
- MA9020** 200-275 mV ORP solution, 230 mL
- SE220** pH electrode with BNC connector and 1 m cable
- SE300** Platinum ORP electrode with 1 m cable



Ordering Information

MW100 PRO and **MW101 PRO** are supplied complete with a SE220 pH electrode, pH 7.01 20 mL sachet of calibration solution, calibration screwdriver, 9V battery and instructions.

MW102 PRO+ is supplied complete with a SE220 pH electrode, MA830R stainless steel temperature probe, pH 4.01 and pH 7.01 20 mL sachet of calibration solution, 9V battery and instructions.

MW500 PRO is supplied complete with a SE300 platinum electrode, 9V battery and instructions.

Measuring pH in soil

Using MW101 PRO pH Portable Meter with a MA920B/1 pH Electrode for measuring pH in SOIL

pH is a measure of the activity of the hydrogen ion (H^+) in the soil solution. If the concentration of H^+ is high, the medium is said to be acid. If it is low, it is said to be alkaline. Most agricultural soils are found between the range of 4 to 10 (when measured in water).

For practical purposes, soil is neutral when pH is between 6 to 8, depending on plant requirements, and it is acidic when pH is less than 6 and alkaline when it is greater than 8.



1. Collect samples of soil.
Take samples from a homogeneous area per 1000m². In smaller places it is also suggested to take at least two samples (the more samples, the more accurate the measurement will be).
Don't take samples from soil where are obvious disorders.

Amount of sample:

Use the same amount of soil for every sample (for example: use identical size sachets)



Spot of sample:

General: take the top 5 cm of the ground
Annuals: from 20-40 cm deep
Fruits: from 20-60 cm deep

Spread the soil on a paper and let it dry out in a shaded place, or put it into a 40°C oven.



2. Shred the dry soil and mix the samples.
You will get a homogeneous sample.
It mustn't contain rocks or organic residues.
Take a sample from this mixture for the measurement.



3. Sift the soil through a 2 mm sifter.

4. Weigh out 1 unit soil (100 g is recommended) and put 2 unit (200 g, 2 dl) destillated water to it.



5. Stir it for 30 seconds.
Wait about five minutes.

6. Stir it again then measure the pH of the solution.





Measuring pH in cheese

Using MW101 PRO pH portable meter with a MA920B/1 pH electrode for measuring pH in cheese

The quality of cheese flavor and texture is the result of well-kept pH and temperature. pH makes sure quality standards have been met; in doing so, they are guaranteeing the safety of the cheese production. Most cheeses range from 5.1 to 5.9 in pH. However, this range will have exceptions to certain types of cheeses such as Camembert cheese which has a pH of 7.4.

During the cheese making process, the pH is measured multiple times. Each type of cheese may have a slightly different process and pH level. It is important for manufacturers and companies to be aware of the differences and treat each cheese variety with the quality and care it deserves. Measuring the pH of cheese essentially gives the manufacturer control of the cheese process.

Cheese making process:

For optimal measurement put a sample into a beaker



1. Addition of the starter culture (temperature should stay below 20°C)
pH level (rennet-induced): 5.1 -5.3
pH level (acid-induced): 4.



2. Coagulation (temperature 30°C)
Usually the pH level stay between: 5.35 – 5.45
In certain cases it can be as low as pH 4.



3. Pressing (room temperature: 16-18°C for mild cheeses and 25°C for hard cheeses)
pH will decrease (pH 5.0 – 5.3)



4. Brining in salt solution (temperature of solution: 15°C)
optimal pH level: 5.2
(except soft cheeses like Roquefort where the pH level should be kept at pH 4.7)

During ripening pH level will increase till the optimal ready value. See the table below



Optimal pH values of ready cheeses	
American, mild	4.98
Camembert	7.44
Cheddar	5.90
Cottage	4.75 - 5.02
Cream, Philadelphia	4.10 - 4.79
Dip	5.80
Edem	5.40
Old English	6.15
Roquefort	5.10 - 5.98
Parmesan	5.20 - 5.30
Snippy	5.18 - 5.21
Stilton	5.70
Swiss Gruyere	5.68 - 6.62



pH55 PRO/pH56 PRO

Compact, pocketable, waterproof pH/Temperature testers with replaceable electrode

Water-resistant pH testers with large dual-level LCD that displays pH and temperature (°C or °F). The large display shows readings in an extended range from -2.0 to 16.0 pH (pH56 has a 0.01 pH resolution) and simultaneously shows temperature from -5.0 to 60.0°C or 23.0 to 140.0°F. They have a stability indicator and hold function that freezes the display for easy and accurate recording. The large display also has graphic symbols to guide you through all operations.

Complete with a temperature probe for fast and more precise temperature measurement they compensate automatically for temperature. Calibration is made automatically in 1 or 2 points with memorized standard and NIST buffer sets. Auto power OFF saves battery power after non-use.

The double-junction electrode can be replaced in a very fast and simple way! The modular design allows easy electrode and battery replacement.

Specifications			
		pH55 PRO	pH56 PRO
Range	pH	-2.0 to 16.0 pH	-2.00 to 16.00 pH
	Temp.	-5.0 to 60.0°C / 23.0 to 140.0°F	-5.0 to 60.0°C / 23.0 to 140.0°F
Resolution	pH	0.1 pH	0.01 pH
	Temp.	0.1°C / 0.1°F	0.1°C / 0.1°F
Accuracy (@25°C)	pH	±0.1 pH	±0.05 pH
	Temp.	±0.5°C / ±1°F	±0.5°C / ±1°F
Typical EMC Deviation	pH	±0.1 pH	±0.02 pH
	Temp.	±0.3°C / ±0.6°F	±0.3°C / ±0.6°F
Calibration		automatic, 1 or 2 points with 2 sets of memorized buffers (pH 4.01, 7.01, 10.01 or 4.01, 6.86, 9.18)	automatic, 1 or 2 points with 2 sets of memorized buffers (pH 4.01, 7.01, 10.01 or 4.01, 6.86, 9.18)
Temperature Compensation		automatic from -5 to 60°C	automatic from -5 to 60°C
Probe		Mi56P (replaceable)	Mi56P (replaceable)
Environment		-5 to 50°C / 32 to 122°F; max RH 100%	-5 to 50°C / 32 to 122°F; max RH 100%
Battery Type		4 x 1.5V; IEC LR44, A76 (included)	4 x 1.5V; IEC LR44, A76 (included)
Battery Life		approx. 300 hours of use	approx. 300 hours of use
Auto-off		after 8 minutes of non-use	after 8 minutes of non-use
Packaging dimensions		254 x 67 x 47 mm	254 x 67 x 47 mm
Packaging weight		200 g	200 g



Accessories

- | | |
|--|---|
| Mi56P Replaceable electrode for pH55 & pH56 | M10010B pH 10.01 buffer solution 20 mL sachet (25 pcs) |
| M10000B Electrode rinse solution, 20 mL sachet (25 pcs) | MA9004 pH 4.01 buffer, 230 mL bottle |
| M10004B pH 4.01 buffer solution 20 mL sachet (25 pcs) | MA9007 pH 7.01 buffer solution, 230 mL bottle |
| M10007B pH 7.01 buffer solution 20 mL sachet (25 pcs) | MA9010 pH 10.01 buffer solution, 230 mL bottle |
| | MA9015 Electrode storage solution, 230 mL |
| | MA9016 Electrode cleaning solution, 230 mL |
| | MA753 Hard carrying case for 2 testers |

Ordering Information

pH55 PRO and pH56 PRO is supplied complete in a carton box with protective cap, 20 mL pH 4.01 and pH 7.01 sachets of calibration solution.

Optionally pH55 PRO is also available in a kit (Mi5559 or Mi5560) together with EC59 PRO or EC60 PRO EC/TDS/Temp Meters.

pH/Temperature Sensor

The pH55 PRO and pH56 PRO's exposed temperature sensor provides fast response time, and its proximity to the pH electrode guarantees much more accurate temperature compensated readings.



Replaceable electrode

Replace the electrode in a fast and simple way yourself! Just unscrew the plastic ring on the top of the electrode and replace the electrode with a new one.



- 2 Years warranty
- ATC
- IP65
- 2 Points
- AUTO Buffer
- Dual Display
- Self diagnostics
- CE
- Electrode replacement



ORP57 PRO/pH58 MAX

Pocket-size pH/ORP/Temperature Meters with replaceable electrode

Combination water-resistant testers with advanced functions also include the model **pH58 MAX** for simultaneous pH and ORP measurements and temperature, which is continuously displayed on the dual level LCD. It shows readings in an extended range from -2.00 to 16.00 pH or ± 1000 mV and simultaneously shows temperature from -5.0 to 105.0°C or 23 to 221°F.

The **pH58 MAX** has a stability indicator and hold feature that freezes the display for easy and accurate recording. The large display also has graphic symbols to guide you through all operations. Calibration is performed automatically at 1 or 2 points using standard or NIST buffers.

The modular design allows easy electrode and battery replacement.



Specifications		ORP57 PRO	pH58 MAX
Range	pH ORP Temp.	± 1000 mV -5.0 to 60.0°C / 23.0 to 140.0°F	-2.00 to 16.00 pH ± 1000 mV -5.0 to 60.0°C / 23.0 to 140.0°F
Resolution	pH ORP Temp.	1 mV 0.1°C / 0.1°F	0.01 pH 1 mV 0.1°C / 0.1°F
Accuracy (@25°C)	pH ORP Temp.	± 2 mV $\pm 0.5^\circ\text{C}$ / $\pm 1^\circ\text{F}$	± 0.05 pH ± 2 mV $\pm 0.5^\circ\text{C}$ / 1°F
Typical EMC Deviation	pH ORP Temp.	± 2 mV $\pm 0.3^\circ\text{C}$ / $\pm 0.6^\circ\text{F}$	± 0.02 pH ± 2 mV $\pm 0.3^\circ\text{C}$ / $\pm 0.6^\circ\text{F}$
pH Calibration			automatic for pH, 1 or 2 points from -5 to 60°C with 2 sets of memorized buffers (pH 4.01, 7.01, 10.01 or 4.01, 6.86, 9.18)
ORP Calibration		factory calibrated	factory calibrated
Probe		MI57P (replaceable)	MI58P (replaceable)
Environment		0 to 50°C; max RH 100%	-5 to 50°C; max RH 100%
Battery Type		4 x 1.5V; IEC LR44, A76	4 x 1.5V; IEC LR44, A76
Battery Life		approx. 300 hours of use	approx. 250 hours of use
Auto-off		after 8 minutes of non-use	after 8 minutes of non-use
Packaging dimensions		254 x 67 x 47 mm	254 x 67 x 47 mm
Packaging weight		140 g	200 g

Replaceable combination pH/ORP electrode for pH58

Replace the electrode in a fast and simple way yourself! Just unscrew the plastic ring on the top of the electrode and replace the electrode with a new one.



Calibration, Maintenance & Cleaning Solutions

Choose from our wide selection of calibration, maintenance and cleaning solutions at page 52.



Accessories

- MI57P** Replaceable electrode for ORP57
- MI58P** Replaceable electrode for pH58
- M10000B** Electrode rinse solution, 20 mL sachet (25 pcs)
- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution 20 mL sachet (25 pcs)



- MA9004** pH 4.01 buffer solution, 230 mL bottle
- MA9007** pH 7.01 buffer solution, 230 mL bottle
- MA9010** pH 10.01 buffer solution, 230 mL bottle
- MA9015** Electrode storage solution, 230 mL
- MA9016** Electrode cleaning solution, 230 mL
- MA9020** ORP test solution (200/275 mV), 230 mL bottle
- MA753** Hard carrying case for 2 testers

Ordering Information

ORP57 PRO is supplied in a carton box complete with protective cap, batteries and instructions.

pH58 MAX is supplied in a carton box complete with protective cap, 20 mL pH 4.01 and pH 7.01 sachets of calibration solution, batteries and instructions.

pH51/pH54

Pocket-size Waterproof pH Meters

with replaceable electrode and manual calibration

Waterproof budget pH testers. Their waterproof casing and double junction replaceable electrodes make them suitable also for heavy duty applications, such as wastewater treatment and agriculture.

The modular design allows easy electrode and battery replacement.

Manual calibration prolongs the battery life up to 1500 hours.

Specifications	pH51	pH54
Range	0.0 to 14.0 pH	0.00 to 14.00 pH
Resolution	0.1 pH	0.01 pH
Accuracy (@25°C)	±0.1 pH	±0.1 pH
Typical EMC Deviation	±0.1 pH	±0.1 pH
Calibration	manual at 2 points through trimmers	manual at 2 points through trimmers
pH electrode	MA73600 (replaceable)	MA73600 (replaceable)
Environment	0 to 50°C; max RH 100%	0 to 50°C; max RH 100%
Battery Type	3 x 1.5V alkaline	3 x 1.5V alkaline
Battery Life	more than 1500 hours of continuous use	more than 1500 hours of continuous use
Packaging dimensions	254 x 67 x 47 mm	254 x 67 x 47 mm
Packaging weight	186 g	186 g

Accessories

MA73600 Replaceable electrode for pH51 and pH54

M10000B Electrode rinse solution, 20 mL sachet (25 pcs)

M10004B pH 4.01 buffer solution 20 mL sachet (25 pcs)

M10007B pH 7.01 buffer solution 20 mL sachet (25 pcs)

M10010B pH 10.01 buffer solution 20 mL sachet (25 pcs)

MA9015 Electrode storage solution, 230 mL
MA753 Hard carrying case for 2 testers

Ordering Information

All testers are supplied in a carton box complete with calibration solution, batteries, instruction manual and screwdriver for calibration.

Packaging Information

Optionally pH51 is also available in a kit (**Mi5165**, **Mi5166**, **Mi5175**, **Mi5176**) together with **C65**, **C66**, **T75** or **T76**.



Ordering Information

pH600 is supplied in a plastic hard carrying case, complete with protective cap, calibration screwdriver, batteries and instructions.

pH600

pH Economical Pocket Tester

Milwaukee's budget pH tester with 1 point calibration is an easy-to-use instrument for applications such as aquarium, swimming pool and hydroponics.

Specifications	pH600
Range	0.0 to 14.0 pH
Resolution	0.1 pH
Accuracy	±0.1 pH
Calibration	manual, 1 point
Environment	0 to 50°C / 32 to 122°F; max RH 95%
Battery Type / Battery Life	3 x 1.5V alkaline / 700 hours of use
Packaging dimensions	180 x 65 x 32 mm
Packaging weight	120 g



Accessories

M10004B pH 4.01 buffer solution 20 mL sachet (25 pcs)

M10007B pH 7.01 buffer solution 20 mL sachet (25 pcs)

M10010B pH 10.01 buffer solution, 20 mL sachet (25 pcs)

MA9015 Electrode storage solution, 230 mL

MA9016 Electrode cleaning solution, 230 mL



MC110 PRO/MC120 PRO pH Monitors

PRO pH monitor allows you to continuously monitor pH values directly in your reservoir. Features include: user selectable set point, visual LED alarm when values go above or below the set point and manual calibration. Each monitor is powered by a 12 VDC adapter and is ideal for applications such as Hydroponics and Aquarium.

The pH monitors are very simple to operate:

1. Hang your monitor above the reservoir;
2. Connect the adapter to the meter and plug in the power supply (make sure that your power supply is in a safe area away from the water);
3. Immerse 2/3 of the electrode in the solution;
4. The probe can now remain there permanently.

The monitors are supplied complete with a MA911B/2 pH electrode. Each monitor comes complete with a 12 VDC adapter and calibration solution.



Specifications	MC110 PRO	MC120 PRO
Range	0.0 to 14.0 pH	0.0 to 14.0 pH
Resolution	0.1 pH	0.1 pH
Accuracy (@25°C)	±0.2 pH	±0.2 pH
Calibration	manual, 2 points through trimmers on the meter front panel	manual, 2 points through trimmers on the meter front panel
Set point	3.5 to 7.5 pH	5.5 to 9.5 pH
Alarm	active when measurement is higher or lower than selected set point	active when measurement is higher or lower than selected set point
pH Electrode	MA911B/2 (included)	MA911B/2 (included)
Environment	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%
Power supply	12 VDC power adapter (included)	12 VDC adapter
Packaging dimensions	268 x 122 x 118 mm	268 x 122 x 118 mm
Packaging weight	820 g	820 g

Accessories



- M10000B** Electrode rinse solution, 20 mL sachet (25 pcs)
- M10004B** pH 4.01 buffer solution, 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution, 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution, 20 mL sachet (25 pcs)
- M10016B** Electrode cleaning solution, 20 mL sachet (25 pcs)
- MA9015** Electrode storage solution, 20 mL sachet (25 pcs)
- MA9016** Electrode cleaning solution, 20 mL sachet (25 pcs)
- MA9310** 12 VDC Adapter, 220 V
- MA9311** 12 VDC Adapter, 110 V
- MA911B/2** Double junction, gel filled pH electrode with 2 m cable



User selectable Hi/Low Set Point

A visual LED alarms when value goes above or below the set point the user selected.



Ordering Information

MC110 PRO is supplied complete with MA9310 12VDC adapter, MA911B/2 pH electrode, 20 mL pH 7.01 sachet of calibration solution, calibration screwdriver and instructions, in a carton box.

MC120 PRO is supplied complete with MA9310 12VDC adapter, MA911B/2 pH electrode, 20 mL pH 7.01 sachet of calibration solution, calibration screwdriver and instructions, in a carton box.

MC122 PRO/MC510 PRO/MC125 PRO pH & ORP Controllers

With Milwaukee's MC Controllers you can monitor and control pH and/or ORP levels.

The Milwaukee Instruments MC Controllers have a user selectable set point and a visual "Power Activated" LED notification light. Power to the controller box is turned on when the reading is Above or Below the selected set point. These MC Controllers are ideal for CO₂ or ozone dosing. This could be controlled by a solenoid valve (MA955).

With each Milwaukee PRO controller, your aquarium will have the individual attention that it needs.

Each unit comes with 12 VDC adapter, mounting kit, probe and starter calibration solution for pH (factory calibrated for ORP).

Professional pH controller especially designed for use in aquariums and hydroponic systems.



MA955 Solenoid valve for CO₂ dosing

Key features include:

- User selectable Hi/Low Set Point
- Manual 2 points calibration
- Visual LED alarm
- Supplied with 12 VDC adapter and mounting kit
- Power plug for CO₂ dosing
- Double junction pH electrode and/or platinum ORP electrode (BNC connector)

Specifications	MC122 PRO	MC510 PRO	MC125 PRO
Range	0.0 to 14.0 pH	±1000 mV (ORP)	0.00 to 14.00 pH; ±1000 mV (ORP)
Resolution	0.1 pH	1 mV (ORP)	0.1 pH; 1 mV (ORP)
Accuracy (@25°C)	±0.2 pH	±5 mV (ORP)	±0.2 pH; ±5 mV (ORP)
Set point pH	5.5 to 9.5 pH		4 to 8 pH
Set point ORP		0 to 600 mV	-200 to 600 mV
Alarm	active when measurement is higher or lower than selected set point	active when measurement is higher or lower than selected set point	active when measurement is higher or lower than selected set points
Output power socket	relay, 230V / 117V; 8A	relay, 230V / 117V; 8A	relay, 230V / 117V; 8A
Output	active when measurement is higher or lower than selected set point	active when measurement is higher or lower than selected set point	active when measurement is higher or lower than selected set points
pH Electrode	MA911B/2 (included)		MA911B/2 (included)
ORP Electrode		MA921B/2 (included)	MA921B/2 (included)
Environment	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%
Power Supply	12 VDC power adapter (included)	12 VDC power adapter (included)	12 VDC power adapter (included)
Power Drivers	115VAC, 2A, 60Hz or 230VAC, 1A, 50Hz	115VAC, 2A, 60Hz or 230VAC, 1A, 50Hz	115VAC, 2A, 60Hz or 230VAC, 1A, 50Hz
Packaging dimensions	276 x 129 x 138 mm	276 x 129 x 138 mm	276 x 129 x 138 mm
Packaging weight	1.1 kg	0.9 kg	1.4 kg

Accessories

- M10000B** Electrode rinse solution 20 mL sachet (25 pcs)
- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution 20 mL sachet (25 pcs)
- MA9015** Electrode storage solution 20 mL sachet (25 pcs)
- MA9310** 12 VDC Adapter, 220 V
- MA9311** 12 VDC Adapter, 110 V
- MA955** Solenoid valve with 1.5 m cable
- MA911B/2** Double junction, gel filled pH electrode with 1 m cable
- MA921B/2** ORP Electrode with BNC connector and 2 m cable

Ordering Information

- MC122 PRO** is supplied complete with MA9310 12 VDC adapter, MA911B/2 pH electrode, 20 mL pH4.01 sachet of calibration solution, 20 mL pH7.01 sachet of calibration solution, calibration screwdriver and instructions, in a carton box.
- MC510 PRO** is supplied complete with MA9310 12 VDC adapter, MA921B/2 ORP electrode and instructions, in a carton box.
- MC125 PRO** is supplied complete with MA9310 12 VDC adapter, power plug socket for ozone dosing, MA911B/2 pH electrode, MA921B/2 ORP electrode, 20 mL pH7.01 sachet of calibration solution, calibration screwdriver and instructions, in a carton box.



Control the pH of your tank/reservoir **AUTOMATICALLY!**



The **MC122 PRO** pH controller and dosing pump (**MP810/MP815**) provides fully automated pH control of aqueous solutions in hydroponic systems. It has been specifically designed to control the pH in mixing tanks for fertirrigation. The small and precise flow of the peristaltic pump allows you to maintain ideal pH values in your tank.

After selecting the desired pH setting from 5.5 to 9.5 pH, the pH controller measures the pH value of the solution and automatically adds pH adjustment (acid or alkaline) to change the liquid's pH to the selected level.

The **MP815** pump is with adjustable flow rate and dosing can be reduced by using a timer to turn the pump on and off at regular intervals.

Specifications	MP810	MP810 US
Max. Flow	1.5 L/h	0.6 L/h
Max. Pressure	2 bar	1.5 bar
Squeeze tubing	Santoprene	Santoprene
Ext. Tube connection	6 mm	6 mm
Power supply	240 VAC, 50-60 Hz	110 VAC, 60 Hz
Power consumption	7.7 W	0.42 W
Packaging dimensions	138 x 165 x 123 mm	138 x 165 x 123 mm
Packaging weight	820 g	620 g

Specifications	MP815	MP815 US
Adjustable Flow	0.0 to 2.2 L/h	0.0 to 2.2 L/h
Max. Pressure	2 bar	1.5 bar
Squeeze tubing	Santoprene	Santoprene
Ext. Tube connection	6 mm	6 mm
Power supply	240 VAC, 50-60 Hz	110 VAC, 60 Hz
Power consumption	7.7 W	0.42 W
Packaging dimensions	138 x 165 x 123 mm	138 x 165 x 123 mm
Packaging weight	820 g	620 g



MC122 PRO pH Controller

Ordering Information

MP810 and **MP815** are supplied complete with mounting bracket, screws, 1.5 meter Ext. PE tubing, Filter, Fitting, 2,6 meter Power cable.

MC122 PRO is supplied complete with MA9310 12 VDC adapter, MA911B/2 pH electrode, 20 mL pH4.01 sachet of calibration solution, 20 mL pH7.01 sachet of calibration solution, calibration screwdriver and instructions.

You can also order **MC122 PRO** with **MP810** in a kit (**MC720**).

Accessories

- M10000B** Electrode rinse solution 20 mL sachet (25 pcs)
- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution 20 mL sachet (25 pcs)



- MA9015** Electrode storage solution 20 mL sachet (25 pcs)
- MA9310** 12 VDC Adapter, 220 V
- MA9311** 12 VDC Adapter, 110 V
- MA911B/2** Double junction, gel filled pH electrode with 1 m cable



MC720 kit, including MC122 pH Controller and MP810 Dosing Pump

MW170 MAX

Autoranging EC/TDS/NaCl/Temperature Laboratory Bench Meter

MW170 MAX is a compact and versatile bench meter that can measure up to four different parameters: EC, TDS, salinity (in PSU, g/L, percentage NaCl) and temperature. The main operating modes are setup, calibration, measurement and logging.

- Easy to read LCD display
- Auto-off feature to prolong battery life
- All measurements can be temperature compensated automatically (ATC), or manually (MTC) with a user-selectable compensation coefficient. Temperature compensation can be disabled (NO TC) if the actual conductivity value is required.
- The auto-ranging feature for both EC and TDS measurements automatically sets the most suitable resolution for the tested sample.
- Available log space for up to 1000 records. Logged data can be exported using a USB cable
- Dedicated GLP key to store and recall data on system status
- Built-in rechargeable battery with 8 hours battery life



Specifications	MW170 MAX						
Range	<table border="0"> <tr> <td>EC</td> <td>0.00 to 29.99 µS/cm; 30.0 to 299.9 µS/cm; 300 to 2999 µS/cm; 3.00 to 29.99 mS/cm; 30.0 to 200.0 mS/cm; up to 500.0 mS/cm absolute conductivity*</td> </tr> <tr> <td>TDS</td> <td>0.00 to 14.99 mg/L (ppm); 15.0 to 149.9 mg/L (ppm); 150 to 1499 mg/L (ppm); 1.5 to 14.99 g/L (ppt); 15.0 to 100.0 g/L (ppt); up to 400.0 g/L absolute TDS* (with 0.80 factor)</td> </tr> <tr> <td>Salinity Temp</td> <td>0.0 to 400.0 ‰ NaCl; 2.00 to 42.00 PSU; 0.00 to 80.00 g/L -20.0 to 120.0°C / -4.0 to 248.0°F</td> </tr> </table>	EC	0.00 to 29.99 µS/cm; 30.0 to 299.9 µS/cm; 300 to 2999 µS/cm; 3.00 to 29.99 mS/cm; 30.0 to 200.0 mS/cm; up to 500.0 mS/cm absolute conductivity*	TDS	0.00 to 14.99 mg/L (ppm); 15.0 to 149.9 mg/L (ppm); 150 to 1499 mg/L (ppm); 1.5 to 14.99 g/L (ppt); 15.0 to 100.0 g/L (ppt); up to 400.0 g/L absolute TDS* (with 0.80 factor)	Salinity Temp	0.0 to 400.0 ‰ NaCl; 2.00 to 42.00 PSU; 0.00 to 80.00 g/L -20.0 to 120.0°C / -4.0 to 248.0°F
EC	0.00 to 29.99 µS/cm; 30.0 to 299.9 µS/cm; 300 to 2999 µS/cm; 3.00 to 29.99 mS/cm; 30.0 to 200.0 mS/cm; up to 500.0 mS/cm absolute conductivity*						
TDS	0.00 to 14.99 mg/L (ppm); 15.0 to 149.9 mg/L (ppm); 150 to 1499 mg/L (ppm); 1.5 to 14.99 g/L (ppt); 15.0 to 100.0 g/L (ppt); up to 400.0 g/L absolute TDS* (with 0.80 factor)						
Salinity Temp	0.0 to 400.0 ‰ NaCl; 2.00 to 42.00 PSU; 0.00 to 80.00 g/L -20.0 to 120.0°C / -4.0 to 248.0°F						
Resolution	<table border="0"> <tr> <td>EC</td> <td>0.01 µS/cm; 0.1 µS/cm; 1.0 µS/cm; 0.01 mS/cm; 0.1 mS/cm</td> </tr> <tr> <td>TDS</td> <td>0.01 mg/L; 0.1 mg/L; 1.0 mg/L; 0.01 g/L; 0.1 g/L</td> </tr> <tr> <td>Salinity Temp</td> <td>0.1% NaCl; 0.01 PSU; 0.01 g/L 0.1°C / 0.1°F</td> </tr> </table>	EC	0.01 µS/cm; 0.1 µS/cm; 1.0 µS/cm; 0.01 mS/cm; 0.1 mS/cm	TDS	0.01 mg/L; 0.1 mg/L; 1.0 mg/L; 0.01 g/L; 0.1 g/L	Salinity Temp	0.1% NaCl; 0.01 PSU; 0.01 g/L 0.1°C / 0.1°F
EC	0.01 µS/cm; 0.1 µS/cm; 1.0 µS/cm; 0.01 mS/cm; 0.1 mS/cm						
TDS	0.01 mg/L; 0.1 mg/L; 1.0 mg/L; 0.01 g/L; 0.1 g/L						
Salinity Temp	0.1% NaCl; 0.01 PSU; 0.01 g/L 0.1°C / 0.1°F						
Accuracy (@ 25 °C / 77 °F)	<table border="0"> <tr> <td>EC</td> <td>±1% of reading (±0.05 µS/cm or 1 digit, whichever is greater)</td> </tr> <tr> <td>TDS</td> <td>±1% of reading (±0.03 ppm or 1 digit, whichever is greater)</td> </tr> <tr> <td>Salinity Temp</td> <td>±1% of reading ±0.5 °C; ±0.9 °F</td> </tr> </table>	EC	±1% of reading (±0.05 µS/cm or 1 digit, whichever is greater)	TDS	±1% of reading (±0.03 ppm or 1 digit, whichever is greater)	Salinity Temp	±1% of reading ±0.5 °C; ±0.9 °F
EC	±1% of reading (±0.05 µS/cm or 1 digit, whichever is greater)						
TDS	±1% of reading (±0.03 ppm or 1 digit, whichever is greater)						
Salinity Temp	±1% of reading ±0.5 °C; ±0.9 °F						
Calibration	<table border="0"> <tr> <td>EC/TDS</td> <td>Single cell factor calibration 6 standards: 84 µS/cm, 1413 µS/cm, 5.00 mS/cm, 12.88 mS/cm, 80.0 mS/cm, 111.8 mS/cm one-point offset: 0.00 µS/cm</td> </tr> <tr> <td>Salinity Temp</td> <td>one-point with MA9066 Salinity calibration solution 2 points, 0 to 50°C / 32 to 122°F</td> </tr> </table>	EC/TDS	Single cell factor calibration 6 standards: 84 µS/cm, 1413 µS/cm, 5.00 mS/cm, 12.88 mS/cm, 80.0 mS/cm, 111.8 mS/cm one-point offset: 0.00 µS/cm	Salinity Temp	one-point with MA9066 Salinity calibration solution 2 points, 0 to 50°C / 32 to 122°F		
EC/TDS	Single cell factor calibration 6 standards: 84 µS/cm, 1413 µS/cm, 5.00 mS/cm, 12.88 mS/cm, 80.0 mS/cm, 111.8 mS/cm one-point offset: 0.00 µS/cm						
Salinity Temp	one-point with MA9066 Salinity calibration solution 2 points, 0 to 50°C / 32 to 122°F						
Temp. Compensation	ATC – automatic, from -5 to 100 °C (23 to 212 °F) MTC – manual, from -5 to 100 °C (23 to 212 °F) No TC – without temperature compensation						
Temp. Coefficient	0.00 to 6.00 % / °C (EC & TDS only) Default value: 1.90 % / °C						
Probe	MA814DB/1 4-ring probe with built-in temperature sensor (included)						
TDS Factor	0.40 to 0.80 Default value: 0.50						
Log	Maximum 1000 records; On demand, max. 200 samples; On stability, max. 200 samples Interval logging, max. 1000 samples (max. 100 lots)						
PC connectivity	1 micro USB port						
Environment	0 to 50 °C; max RH 95%						
Power supply	12 VDC adapter (included)						
Battery life	8 hours						
Packaging dimensions	335 x 120 x 255 mm						
Packaging weight	2.16 kg						

(*) Absolute conductivity (or TDS) is the conductivity value without temperature compensation.

More accurate readings with the 4-RING MA814DB/1 EC/TDS/NaCl and Temperature probe!

Conductivity readings are performed by applying an alternate current to the 4-ring probe which creates a variable voltage depending on the conductivity.



Rear Connector Panel layout

Communication to the PC is done via a micro USB port.



Accessories

- MA814DB/1** EC/Temperature probe with DIN connector and 1 m cable
- MA9060** 12880 µS/cm calibration solution, 230 mL bottle
- MA9061** 1413 µS/cm calibration solution, 230 mL bottle
- MA9063** 84 µS/cm calibration solution, 230 mL bottle
- MA9064** 80000 µS/cm conductivity solution, 230 mL bottle



- MA9065** 111.8 mS/cm calibration solution, 230 mL bottle
- MA9066** 100% NaCl calibration solution, 230 mL bottle
- MA9069** 5000 µS/cm solution, 230 mL bottle
- MA9310** 12 VDC Adapter, 220 V
- MA9311** 12 VDC Adapter, 110 V
- MA9315** Electrode holder
- MA9350** RS232 connection cable with 2 meters cable

Ordering Information

- MW170 MAX** is supplied complete with
- **MA814DB/1** EC/TDS/NaCl/Temperature Probe
 - **MA9315** Electrode Holder
 - **MA9310** 12 VDC Adapter
 - Instruction manual

- 2 Year warranty
- LOG
- USB
- ATC
- MTC
- Self-Diagnostics
- CE
- IP67
- GLP



MW306 MAX

Automatic & Logging EC/TDS/NaCl/Temperature Meter

MW306 MAX is a waterproof and portable meter with a user-friendly interface. Designed to measure four different parameters – EC, TDS, percentage of salinity in psu (NaCl%) and temperature – the meter is suitable for multiple applications.

- IP67 waterproof casing
- Data logging: 1000 logs can be stored in the built-in memory including readings, GLP data, date and time
- Different logging methods: manual log-on-demand (max. 200 logs); manual log-on-stability (max. 200 logs) and interval log (max. 600 samples; 100 lots)
- auto-ranging feature for both EC and TDS measurements automatically sets the most suitable resolution for the tested sample.
- GLP data review and the data can be transferred to a PC through a USB port.

Hard Carrying Case

The meter is supplied in a hard carrying case ideal for field measurements.



Specifications	MW306 MAX
Range	<p>EC 0.00 to 29.99 $\mu\text{S/cm}$; 30.0 to 299.9 $\mu\text{S/cm}$; 300 to 2999 $\mu\text{S/cm}$; 3.00 to 29.99 mS/cm; 30.0 to 200.0 mS/cm; up to 500.0 mS/cm absolute EC*</p> <p>TDS 0.00 to 14.99 mg/L; 15.0 to 149.9 mg/L; 150 to 1499 mg/L; 1.50 to 14.99 g/L; 15.0 to 100.0 g/L; up to 400.0 g/L absolute (*) TDS (with 0.80 factor)</p> <p>Salinity 0.0 to 400.0 % NaCl 2.00 to 42.00 PSU</p> <p>Temp 0.00 to 80.00 $^{\circ}\text{C}$ -20.0 to 120.0 $^{\circ}\text{C}$; -4.0 to 248.0 $^{\circ}\text{F}$</p>
Resolution	<p>EC 0.01 $\mu\text{S/cm}$; 0.1 $\mu\text{S/cm}$; 1 $\mu\text{S/cm}$; 0.01 mS/cm; 0.1 mS/cm</p> <p>TDS 0.01 mg/L; 0.1 mg/L; 1 mg/L; 0.01 g/L; 0.1 g/L</p> <p>Salinity 0.1% NaCl; 0.01 PSU; 0.01 g/L</p> <p>Temp 0.1 $^{\circ}\text{C}$; 0.1 $^{\circ}\text{F}$</p>
Accuracy (@ 25 $^{\circ}\text{C}$ / 77 $^{\circ}\text{F}$)	<p>EC $\pm 1\%$ of reading ($\pm 0.05 \mu\text{S/cm}$ or 1 digit, whichever is greater)</p> <p>TDS $\pm 1\%$ of reading ($\pm 0.03 \text{ ppm}$ or 1 digit, whichever is greater)</p> <p>Salinity $\pm 1\%$ of reading</p> <p>Temp $\pm 0.5 \text{ }^{\circ}\text{C}$; $\pm 0.9 \text{ }^{\circ}\text{F}$</p>
Calibration	<p>EC/TDS Single cell factor calibration 6 standards: 84 $\mu\text{S/cm}$, 1413 $\mu\text{S/cm}$, 5.00 mS/cm, 12.88 mS/cm, 80.0 mS/cm, 111.8 mS/cm one-point offset: 0.00 $\mu\text{S/cm}$ one-point with MA9066 Salinity calibration solution</p> <p>Salinity MA9066 Salinity calibration solution</p>
Temperature Compensation	<p>ATC – automatic, from -5 to 100 $^{\circ}\text{C}$ (23 to 212 $^{\circ}\text{F}$)</p> <p>MTC – manual, from -20 to 120 $^{\circ}\text{C}$ (23 to 212 $^{\circ}\text{F}$)</p> <p>NO TC – without temperature compensation</p>
Temperature Coefficient	0.00 to 6.00 % / $^{\circ}\text{C}$ (EC & TDS only) Default value: 1.90 % / $^{\circ}\text{C}$
TDS Factor	0.40 to 0.80 Default value: 0.50
EC Probe	MA815D/1
Log	<p>Max. 1000 log records (stored in up to 100 lots)</p> <p>On demand, 200 logs / On stability, 200 logs / Interval logging, 1000 logs</p>
PC connectivity	1 micro USB port
Power supply	12 VDC adapter (included)
Battery life	Approx. 200 hours of use
Auto-off	5, 10, 30, 60 minutes or off
Environment	0 to 50 $^{\circ}\text{C}$; max RH 95%
Casing	IP67
Packaging dimensions	305 x 280 x 115 mm
Packaging weight	1.22 kg

(*) Absolute conductivity (or TDS) is the conductivity value without temperature compensation.

Accessories



- MA815D/1** 4-ring EC/TDS/NaCl/Temperature probe with DIN connector and 1 meter cable
- M10030B** 12880 $\mu\text{S/cm}$ calibration solution, 20 mL sachet, 25 pcs.
- M10031B** 1413 $\mu\text{S/cm}$ calibration solution, 20 mL sachet, 25 pcs.
- M10035B** 111.8 mS/cm calibration solution, 20 mL sachet, 25 pcs.
- MA9060** 12880 $\mu\text{S/cm}$ calibration solution, 230 mL bottle
- MA9061** 1413 $\mu\text{S/cm}$ calibration solution, 230 mL bottle
- MA9063** 84 $\mu\text{S/cm}$ calibration solution, 230 mL bottle
- MA9065** 111.8 mS/cm calibration solution, 230 mL bottle
- MA9066** 100% NaCl calibration solution, 230 mL bottle
- MA9069** 5000 $\mu\text{S/cm}$ solution, 230 mL bottle

Ordering Information

MW306 MAX is supplied in a hard carrying case complete with

- **MA815D/1** 4-ring EC/TDS/NaCl/Temperature probe with DIN connector and 1 meter cable
- **MA9316** electrode holder
- 12 VDC adapter
- Micro USB cable
- Instrument quality certificate
- Instruction manual

MW301 PRO/MW302 PRO/MW401 PRO/MW402 PRO

Budget Conductivity & TDS

Portable Meters for fast and reliable results

MW301 PRO, MW302 PRO, MW401 PRO and MW402 PRO are compact microprocessor-based Conductivity and TDS Portable Meters. These handy and ergonomically designed portable meters are ideal for anyone working on a low budget and still requires fast and reliable measurements.

These portable meters are suitable for a wide range of applications, such as Educational, Agriculture and Horticulture, as well as water and environmental analysis.

These portable meters with Automatic Temperature Compensation have a small and ergonomic case design. Other features include large and easy to read LCD and long battery life. Each meter is supplied complete with Conductivity/TDS probe with 1 meter cable and calibration solution.

Choose your portable EC & TDS meter according to the proper EC/TDS ranges for your application:

- **MW301 PRO:** 0 to 1999 $\mu\text{S/cm}$ with a 1 $\mu\text{S/cm}$ resolution;
- **MW302 PRO:** 0.0 to 10.0 mS/cm with a 0.1 mS/cm resolution;
- **MW401 PRO:** 0 to 1999 mg/L (ppm) with a 1 mg/L resolution;
- **MW402 PRO:** 0.0 to 10.0 g/L (ppt) with a 0.1 g/L resolution.



Specifications	MW301 PRO 	MW302 PRO 	MW401 PRO 	MW402 PRO 
Range	0 to 1999 $\mu\text{S/cm}$	0.0 to 10.0 mS/cm	0 to 1999 mg/L (ppm)	0.0 to 10.0 g/L (ppt)
Resolution	1 $\mu\text{S/cm}$	0.1 mS/cm	1 mg/L (ppm)	0.1 g/L (ppt)
Accuracy (@25°C)	$\pm 2\%$ Full Scale	$\pm 2\%$ Full Scale	$\pm 2\%$ Full Scale	$\pm 2\%$ Full Scale
Conversion factor			0.5	0.5
Calibration Solutions (included)	1413 $\mu\text{S/cm}$ (M10031B)	5.00 mS/cm (M10039B)	1382 mg/L (M10032B)	6.44 g/L (M10038B)
Conductivity probe	SE510 (included)	SE520 (included)	SE510 (included)	SE520 (included)
Temperature Compensation	automatic, from 5 to 50°C	automatic, from 5 to 50°C	automatic, from 5 to 50°C	automatic, from 5 to 50°C
Environment	0 to 50°C, max RH 95%	0 to 50°C, max RH 95%	0 to 50°C, max RH 95%	0 to 50°C, max RH 95%
Battery Type	1 x 9V alkaline (included)	1 x 9V alkaline (included)	1 x 9V alkaline (included)	1 x 9V alkaline (included)
Battery Life	approx. 300 hours of use	approx. 300 hours of use	approx. 300 hours of use	approx. 300 hours of use
Packaging dimensions	212 x 145 x 67 mm	212 x 145 x 67 mm	212 x 145 x 67 mm	212 x 145 x 67 mm
Packaging weight	440 g	440 g	440 g	440 g

Accessories

- SE510** EC/TDS probe with DIN connector and 1 m cable for MW301, MW401
- SE520** EC/TDS probe with DIN connector and 1 m cable for MW302, MW402
- M10031B** 1413 $\mu\text{S/cm}$ calibration solution, 20 mL (25 pcs)
- M10032B** 1382 ppm (mg/L) calibration solution, 20 mL (25 pcs)

- M10038B** 6.44 ppt (g/L) calibration solution, 20 mL (25 pcs)
- MA9060** 12880 $\mu\text{S/cm}$ calibration solution, 230 mL bottle
- MA9061** 1413 $\mu\text{S/cm}$ calibration solution, 230 mL bottle
- MA9062** 1382 ppm TDS solution, 230 mL bottle



Packaging Information

MW301 PRO, MW302 PRO, MW401 PRO, MW402 PRO are supplied in a carton color box. Optionally they can be ordered in a hard carrying case (**MA751**).



Ordering Information

- MW301 PRO** is supplied complete with SE510 EC probe, 20 mL 1413 $\mu\text{S/cm}$ sachet of calibration solution, screwdriver for calibration, 9V battery and instructions.
- MW302 PRO** is supplied complete with SE520 EC probe, 20 mL 1413 $\mu\text{S/cm}$ sachet of calibration solution, screwdriver for calibration, 9V battery and instructions.
- MW401 PRO** is supplied complete with SE510 EC probe, 20 mL 1382 ppm sachet of calibration solution, screwdriver for calibration, 9V battery and instructions.
- MW402 PRO** is supplied complete with SE520 EC probe, 20 mL 6.44 ppt sachet of calibration solution, screwdriver for calibration, 9V battery and instructions.

EC59 PRO/EC60 PRO Pocket-size EC/TDS/Temp Meters



Water-resistant pocket-size EC/TDS/Temp meters include features such as replaceable probe, temperature in °C or °F, automatic temperature compensation with adjustable β , battery level indicator, stability indicator, automatic shut-off and automatic calibration all in a floating, water-resistant casing.

EC59 PRO shows on the dual-level LCD the EC (3999 $\mu\text{S}/\text{cm}$) or TDS (2000 ppm) value. It also displays the temperature from 0.0 to 60.0°C (or 32.0 to 140.0°F) on the secondary level at the same time.


EC60 PRO shows on the dual-level LCD the EC (20.00 mS/cm) or TDS (10.00 ppt) value. It also displays the temperature from 0.0 to 60.0°C (or 32.0 to 140.0°F) on the secondary level at the same time.

Specifications	EC59 PRO	EC60 PRO
Range	EC 3999 $\mu\text{S}/\text{cm}$ TDS 2000 ppm Temp 0.0 to 60.0°C / 32.0 to 140.0°F	EC 20.00 mS/cm TDS 10.00 ppt Temp 0.0 to 60.0°C // 32.0 to 140.0°F
Resolution	EC 1 $\mu\text{S}/\text{cm}$ TDS 1 ppm Temp 0.1°C / 0.1°F	EC 0.01 mS/cm TDS 0.01 ppt Temp 0.1°C / 0.1°F
Accuracy (@20°C)	EC $\pm 2\%$ Full Scale TDS $\pm 2\%$ Full Scale Temp $\pm 0.5^\circ\text{C} / \pm 1^\circ\text{F}$	EC $\pm 2\%$ Full Scale TDS $\pm 2\%$ Full Scale Temp $\pm 0.5^\circ\text{C} / \pm 1^\circ\text{F}$
Typical EMC Deviation	EC $\pm 2\%$ Full Scale TDS $\pm 2\%$ Full Scale Temp $\pm 0.5^\circ\text{C} / \pm 1^\circ\text{F}$	EC $\pm 2\%$ Full Scale TDS $\pm 2\%$ Full Scale Temp $\pm 0.5^\circ\text{C} / \pm 1^\circ\text{F}$
Calibration	automatic, 1 point with 1413 $\mu\text{S}/\text{cm}$ calibration solution	automatic, 1 point with 12880 $\mu\text{S}/\text{cm}$ calibration solution
Temperature Compensation	automatic, with $\beta=0.0$ to 2.4%/°C	automatic, with $\beta=0.0$ to 2.4%/°C
Probe	MI59P (replaceable)	MI59P (replaceable)
Environment	0 to 50°C / 32 to 122°F; max RH 100%	0 to 50°C / 32 to 122°F; max RH 100%
Battery Type	4 x 1.5V; IEC LR44, A76 (included)	4 x 1.5V; IEC LR44, A76 (included)
Battery Life	approx. 100 hours of use	approx. 100 hours of use
Auto-off	after 8 minutes of non-use	after 8 minutes of non-use
Packaging dimensions	254 x 67 x 47 mm	254 x 67 x 47 mm
Packaging weight	180 g	180 g

Accessories

- MI59P** Replaceable probe for EC59 & EC60
- M10000B** Rinse solution, 20 mL sachet, 25 pcs
- M10030B** 12880 $\mu\text{S}/\text{cm}$ calibration solution, 20 mL sachet, 25 pcs
- M10031B** 1413 $\mu\text{S}/\text{cm}$ calibration solution, 20 mL sachet, 25 pcs
- M10032B** 1382 ppm (mg/L) calibration solution, 20 mL sachet, (25 pcs)

- M10038B** 6.44 ppt (g/L) calibration solution, 20 mL sachet, (25 pcs)
- MA9060** 12880 $\mu\text{S}/\text{cm}$ calibration solution, 230 mL bottle
- MA9061** 1413 $\mu\text{S}/\text{cm}$ calibration solution, 230 mL bottle
- MA9016** Cleaning solution, 230 mL bottle
- MA753** Hard carrying case for 2 testers



EC/TDS/Temp probe

Exposed temperature sensor

Replaceable EC/TDS probe

Ordering Information

EC59 PRO is supplied in a carton box complete with protective cap, 20 mL 1413 $\mu\text{S}/\text{cm}$ sachet of calibration solution, batteries and instructions.

EC60 PRO is supplied in a carton box complete with protective cap, 20 mL 12880 $\mu\text{S}/\text{cm}$ sachet of calibration solution, batteries and instructions.

Optionally **EC59 PRO** and **EC60 PRO** is also available in a kit (**Mi5559** or **Mi5560**) together with **pH55 PRO** pH/Temp Meter.

Replaceable probe
Replace the probe in a fast and simple way yourself!
Just unscrew the plastic ring on the top of the probe and replace the probe with a new one.



C65/C66/T75/T76

Pocket-size Waterproof Conductivity & TDS testers with replaceable probe and manual calibration

Waterproof testers designed for all applications. Their waterproof casing and replaceable probe make them suitable also for heavy duty applications, such as wastewater treatment and agriculture. The modular design allows easy probe and battery replacement.

Specifications	C65	C66	T75	T76
Range	0 to 1999 µS/cm	0.00 to 10.00 mS/cm	0 to 1999 ppm (mg/L)	0 to 9990 ppm (mg/L)
Resolution	1 µS/cm	0.01 mS/cm	1 ppm (mg/L)	10 ppm (mg/L)
Accuracy	±2% Full Scale	±2% Full Scale	±2% Full Scale	±2% Full Scale
Typical EMC Deviation	±2% Full Scale	±2% Full Scale	±2% Full Scale	±2% Full Scale
Temp. Compensation	automatic, with β=2%/°C	automatic, with β=2%/°C	automatic, with β=2%/°C	automatic, with β=2%/°C
TDS Factor			0.5	0.5
Calibration	manual at 1 point	manual at 1 point	manual at 1 point	manual at 1 point
Probe	MA73075 (replaceable)	MA73075 (replaceable)	MA73075 (replaceable)	MA73076 (replaceable)
Environment	0 to 50°C; max RH 100%	0 to 50°C; max RH 100%	0 to 50°C; max RH 100%	0 to 50°C; max RH 100%
Battery Type	3 x 1.5V alkaline	3 x 1.5V alkaline	3 x 1.5V alkaline	3 x 1.5V alkaline
Battery Life	approx. 250 hours of use	approx. 250 hours of use	approx. 250 hours of use	approx. 250 hours of use
Packaging dimensions	254 x 67 x 47 mm	254 x 67 x 47 mm	254 x 67 x 47 mm	254 x 67 x 47 mm
Packaging weight	157 g	156 g	157 g	156 g

Accessories

- MA73075** Replaceable conductivity probe, LR
- MA73076** Replaceable conductivity probe, HR
- M10000B** Electrode rinse solution, 20 mL sachet (25 pcs)
- M10030B** 12880 µS/cm calibration solution, 20 mL sachet, 25 pcs
- M10031B** 1413 µS/cm calibration solution, 20 mL sachet, 25 pcs
- M10032B** 1382 ppm (mg/L) calibration solution, 20 mL sachet, (25 pcs)
- M10038B** 6.44 ppt (g/L) calibration solution, 20 mL sachet, (25 pcs)
- M10080B** 800 ppm calibration solution, 20 mL sachet (25 pcs)
- MA753** Hard carrying case for 2 testers

Ordering Information

All testers are supplied in a carton box complete with calibration solution, batteries, instruction manual and screwdriver for calibration. Optionally **C65**, **C66**, **T75** and **T76** is also available in a kit (**Mi5165**, **Mi5166**, **Mi5175**, **Mi5176**) together with **pH51** pH Meter.



CD600/CD601/CD610/CD611/CD97

EC & TDS Economical Pocket Testers

Milwaukee's economical testers are easy-to-use and low cost instruments to measure quick and reliable EC or TDS values. Milwaukee provides you with a range of pocket testers that will allow you to measure from very low to very high conductivity solutions. All EC/TDS testers compensate for the temperature variance automatically.

Specifications	CD600	CD601	CD610	CD611	CD97
Range	0 to 1990 ppm	0 to 1990 µS/cm	0 to 10000 ppm	0 to 20000 µS/cm	0 to 1000 ppm
Resolution	10 ppm	10 µS/cm	100 ppm	100 µS/cm	1 ppm
Accuracy	±2% Full scale	±2% Full scale	±2% Full scale	±2% Full scale	±10 ppm
Calibration	manual, 1 point	manual, 1 point	manual, 1 point	manual, 1 point	manual, 1 point
Temp. Comp.	automatic from 5 to 50°C	automatic from 5 to 50°C	automatic from 5 to 50°C	automatic from 5 to 50°C	automatic from 5 to 50°C
Environment	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%
Battery Type	4 x 1.5V alkaline	4 x 1.5V alkaline	4 x 1.5V alkaline	4 x 1.5V alkaline	4 x 1.5V alkaline
Battery Life	350 hours of use	350 hours of use	350 hours of use	350 hours of use	350 hours of use
Packaging dim.	180 x 65 x 32 mm	180 x 65 x 32 mm	180 x 65 x 32 mm	180 x 65 x 32 mm	180 x 65 x 32 mm
Packaging weight	120 g	120 g	120 g	120 g	120 g

Accessories

- M10030B** 12880 µS/cm calibration solution, 20 mL (25 pcs)
- M10031B** 1413 µS/cm calibration solution, 20 mL (25 pcs)
- M10032B** 1382 ppm (mg/L) calibration solution, 20 mL (25 pcs)
- M10038B** 6.44 ppt (g/L) calibration solution, 20 mL (25 pcs)
- MA9015** Electrode storage solution, 230 mL
- MA9016** Electrode cleaning solution, 230 mL

Ordering Information

CD600, **CD601**, **CD610**, **CD611** and **CD97** are supplied in a plastic hard carrying case, complete with protective cap, calibration screwdriver, batteries and instructions.

MC310 PRO/MC410 PRO Conductivity/TDS Monitors



Reliable Conductivity and TDS monitors with Automatic temperature compensation and 1 point manual calibration powered by a 12 VDC adapter. They are ideal for the hydroponic market and allow you to continuously monitor EC or TDS values directly in your reservoir.

Other features include: user selectable set point, visual LED alarm when values go above/below (selectable by the user) the set point.

The monitors are very simple to operate:

1. Hang your monitor above your reservoir
2. Connect the adapter to the meter and plug in the power supply (make sure that your power supply is in a safe area from the water!)
3. Immerse 2/3 of the probe in the solution
4. The probe can now remain there permanently.

User selectable Hi/Low Set Point

A visual LED alarms when value goes above or below the set point the user selected.



Specifications



MC310 PRO



MC410 PRO

Range	0.0 to 10.0 mS/cm	0 to 1990 ppm
Resolution	0.1 mS/cm	10 ppm
Accuracy (@25°C)	±2% Full Scale	±2% Full Scale
Conversion factor		0.7
Set point	1 to 5 mS/cm	100 to 1900 ppm
Alarm	active when the measurement is higher or lower than the set point	active when the measurement is higher or lower than the set point
Temperature compensation	automatic, from 5 to 50°C	automatic, from 5 to 50°C
Environment	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%
Probe	MA812/2 (included)	MA812/2 (included)
Power supply	12 VDC power adapter (included)	12 VDC power adapter (included)
Packaging dimensions	268 x 122 x 118 mm	268 x 122 x 118 mm
Packaging weight	820 g	820 g

Accessories



- M10000B** Electrode rinse solution, 20 mL sachet (25 pcs)
- M10031B** 1413 µS/cm calibration solution, 20 mL sachet (25 pcs)
- M10032B** 1382 ppm calibration solution, 20 mL sachet (25 pcs)
- MA9061** 1413 µS/cm calibration solution, 230 mL bottle
- MA9062** 1382 ppm TDS solution, 230 mL bottle
- MA9310** 12 VDC Adapter, 220 V
- MA9311** 12 VDC Adapter, 110 V
- MA812/2** Conductivity probe with 2 m cable

Ordering Information

MC310 PRO is supplied complete with MA9310 12VDC adapter, MA812/2 EC probe, 20 mL 5.00 mS/cm sachet of calibration solution, screwdriver for calibration and instruction, in a carton box.

MC410 PRO is supplied complete with MA9310 12VDC adapter, MA812/2 TDS probe, 20 mL 1500 ppm sachet of calibration solution, screwdriver for calibration and instruction, in a carton box.



MC311 PRO

Conductivity Controller


MC740 & MC745 control the EC & nutrient dosage in your tank AUTOMATICALLY!

The **MC311 PRO** EC controller and dosing pump (**MP810**) provides fully automated EC control of aqueous solutions in hydroponic systems.

The **MC740** kit contains the **MC311 PRO** controller with one **MP810** dosing pump, the **MC745** kit contains the **MC311 PRO** controller with two **MP810** dosing pumps!

Accessories:

MA812/2 EC probe with 2 meter cable



Specifications	MC311 PRO
Range	0.0 to 10.0 mS/cm
Resolution	0.1 mS/cm
Accuracy (@25°C)	±2% Full scale
Set point	0.8 to 2.8 mS/cm
Alarm	active when measurement is higher or lower than the selected set point
Temp. compensation	automatic
Output	active when measurement is higher or lower than the selected set point
Power supply	12 VDC adapter
Packaging dimensions	278 x 132 x 138 mm
Packaging weight	1.1 kg

EC40 EC Waterproof Nutrient Stick

- Readings are displayed with 20 LEDs graph bar
- Range 0.2 to 4 mS/cm
- The alarm feature is user settable and is displayed on the LED bar
- No calibration required
- Auto-ON/OFF function
- The auto-check feature indicates the battery level
- Waterproof and floating design makes the stick an appropriate tool for stirring nutrient solutions in a bucket/tank



Graphite EC probe with ATC



Specifications	EC40
Range	0.2 to 4 mS/cm 2 to 40 CF 140 to 2800 ppm (0.7) 100 to 2000 ppm (0.5)
Resolution	0.1 mS/cm 1 CF 70 ppm 50 ppm
Accuracy	± 4% of reading ± 1 resolution point
Probe	Graphite probe in ABC+PC body
Temp. compensation	automatic
Battery Type	3 x 1.5V AA alkaline
Battery Life	approx. 3 years
Packaging dimensions	444 x dia 56 mm
Packaging weight	415 g



MW600 PRO Budget Dissolved Oxygen Portable Meter for fast and reliable results

The **MW600 PRO** is a compact microprocessor-based Portable Dissolved Oxygen meter. This handy and ergonomically designed portable meter is ideal for anyone working on a low budget and still requires fast and reliable measurements.

This portable meter measures Dissolved Oxygen with a Polarographic probe and is suitable for a wide range of applications, such as Educational and Aquaculture, as well as water and environmental analysis.

Other features include small and ergonomic case design, large and easy to read LCD, low battery warning, easy to replace screw on cap membranes and long battery life.

MW600 PRO is supplied complete with a MA840 D.O. polarographic probe with 4 meter cable, calibration screwdriver, 2 spare membranes, MA9071 (30 mL) electrolyte solution, battery and instructions.



The **MW600 PRO** calibrates easily in 2 points (at 100% saturated air and in 0 Oxygen solution) and has Automatic Temperature Compensation which guarantees the highest accuracy.

Specifications	MW600 PRO
Range	O ₂ 0.0 to 19.9 mg/L
Resolution	O ₂ 0.1 mg/L
Accuracy (@25°C)	O ₂ ±1.5% Full Scale
Calibration	manual on 2 points (zero and slope)
Temperature Compensation	automatic from 0 to 30°C
Probe	MA840 (included)
Environment	0 to 50°C / 32 to 122°F; max RH 95%
Battery Type	9V alkaline (included)
Battery Life	approximately 70 hours of use
Packaging dimensions	268 x 122 x 118 mm
Packaging weight	880 g

Large and easy-to-read display

MW600 PRO offers highly stable and accurate readings with large LCD display.



ALTITUDE & SALINITY COMPENSATION:

If the sample contains salts or if you are performing the measurements at altitude different from sea level, the readout values must be corrected, taking into account the lower degree of oxygen solubility.

Altitude Compensation: all the readouts are referred to sea level, thus the displayed measurements are higher than the actual values. In fact, altitude affects D.O. concentration by decreasing its value.

The table on the left reports the oxygen solubility at various temperatures and altitudes, based on sea level barometric pressure of 760 mmHg.

This gives an idea of the error that can be introduced at different altitudes and allows to calculate the quantity to be subtracted to correct the reading.

Altitude, Meters above Sea Level								
°C	0 m	300 m	600 m	900 m	1200 m	1500 m	1800 m	°F
0	14.6	14.1	13.6	13.2	12.7	12.3	11.8	32.0
2	13.8	13.3	12.9	12.4	12.0	11.6	11.2	35.6
4	13.1	12.7	12.2	11.9	11.4	11.0	10.6	39.2
6	12.4	12.0	11.6	11.2	10.8	10.4	10.1	42.8
8	11.8	11.4	11.0	10.6	10.3	9.9	9.6	46.4
10	11.3	10.9	10.5	10.2	9.8	9.5	9.2	50.0
12	10.8	10.4	10.1	9.7	9.4	9.1	8.8	53.6
14	10.3	9.9	9.6	9.3	9.0	8.7	8.3	57.2
16	9.9	9.7	9.2	8.9	8.6	8.3	8.0	60.8
18	9.5	9.2	8.7	8.6	8.3	8.0	7.7	64.4
20	9.1	8.8	8.5	8.2	7.9	7.7	7.4	68.0
22	8.7	8.4	8.1	7.8	7.7	7.3	7.1	71.6
24	8.4	8.1	7.8	7.5	7.3	7.1	6.8	75.2
26	8.1	7.8	7.5	7.3	7.0	6.8	6.6	78.8
28	7.8	7.5	7.3	7.0	6.8	6.6	6.3	82.4
30	7.5	7.2	7.0	6.8	6.5	6.3	6.1	86.0
32	7.3	7.1	6.8	6.6	6.4	6.1	5.9	89.6
34	7.1	6.9	6.6	6.4	6.2	6.0	5.8	93.2
36	6.8	6.6	6.3	6.1	5.9	5.7	5.5	96.8
38	6.6	6.4	6.2	5.9	5.7	5.6	5.4	100.4
40	6.4	6.2	6.0	5.8	5.6	5.4	5.2	104.0

Accessories

- MA9070** Zero Oxygen calibration solution, 230 mL bottle
- MA9071** Refilling Electrolyte solution, 230 mL bottle



- MA840** D.O. Probe
- MA841** Spare membrane (5 pcs)
- MA751** Hard carrying case

Ordering Information

MW600 PRO is supplied complete with MA840 probe, 2 spare membranes, 20 mL bottle of electrolyte solution, calibration screwdriver, 9V battery and instructions.



MW801 PRO/MW802 PRO

Budget pH/EC/TDS Combined Portable Meters for fast and reliable results

MW801 PRO and **MW802 PRO** are compact microprocessor-based Portable Meters. These meters allow you to measure pH, EC (conductivity) and TDS with just one instrument and one single probe!



These easy and fast to calibrate portable meters have a small and ergonomic case design. Other features include large and easy to read LCD and long battery life.

Both meters calibrate manually in pH, Conductivity and TDS.

Each meter is supplied with the MA850 interchangeable probe with 1 meter cable to measure pH, Conductivity and TDS. The pH electrode utilizes a fiber junction to reduce contamination when measuring fertilizer solutions.

- The **MW801 PRO** with a Conductivity range that goes up to 1990 $\mu\text{S}/\text{cm}$ and TDS range that goes up to 1990 ppm is an ideal tool for drinking water measurements.
- The **MW802 PRO**, with a conductivity range that goes up to 6.00 mS/cm and the TDS up to 4000 ppm is ideal for testing in crop production.



Specifications			
		MW801 PRO	MW802 PRO
Range	pH	0.0 to 14.0 pH	0.00 to 14.00 pH
	EC	0 to 1990 $\mu\text{S}/\text{cm}$	0.00 to 6.00 mS/cm
	TDS	0 to 1990 ppm	0 to 4000 ppm
Resolution	pH	0.1 pH	0.10 pH
	EC	10 $\mu\text{S}/\text{cm}$	0.10 mS/cm
	TDS	10 ppm	10 ppm
Accuracy (@25°C)	pH	± 0.2 pH	± 0.20 pH
	EC/TDS	$\pm 2\%$ Full Scale	$\pm 2\%$ Full Scale
Calibration Solutions		M10007 (pH 7.01)	M10007 (pH 7.01)
		M10031 (1413 $\mu\text{S}/\text{cm}$)	M10031 (1413 $\mu\text{S}/\text{cm}$)
		M10032 (1382 ppm)	
Conversion Factor		0.5	0.68
Calibration		manual, at 1 point	manual, at 1 point
Temperature Compensation		automatic, from 0 to 50°C	automatic, from 0 to 50°C
Probe		SE600 combination pH/EC/TDS/probe (included)	SE600 combination pH/EC/TDS/probe (included)
Environment		0 to 50°C / 32 to 122°F; max RH 95%	0 to 50°C / 32 to 122°F; max RH 95%
Battery Type		1 x 9V alkaline	1 x 9V alkaline
Battery Life		150 hours of use	150 hours of use
Packaging dimensions		268 x 122 x 118 mm	268 x 122 x 118 mm
Packaging weight		640 g	720 g

Large and easy-to-read display

MW801 PRO and **MW802 PRO** offer highly stable and accurate readings with large LCD.



Combined SE600 pH/EC/TDS Probe

The pH electrode utilizes a fiber junction to reduce contamination when measuring fertilizer solutions.



Accessories

- M10000B** Electrode rinse solution, 20 mL sachet (25 pcs)
- M10004B** pH 4.01 buffer solution, 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution, 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution, 20 mL sachet (25 pcs)
- M10031B** 1413 $\mu\text{S}/\text{cm}$ calibration solution, 20 mL sachet (25 pcs)



- M10032B** 1382 ppm calibration solution, 20 mL sachet (25 pcs)
- MA9015** Electrode storage solution, 230 mL bottle
- MA9016** Cleaning solution, 230 mL bottle
- SE600** pH/EC/TDS spare probe with 1 meter cable

Ordering Information

MW801 PRO is supplied complete with SE600 combination pH/EC/TDS probe, 20 mL sachet pH 7.01 buffer solution, 20 mL 1413 $\mu\text{S}/\text{cm}$ sachet of calibration solution, 20 mL 1382 ppm sachet of calibration solution, 9V battery and instructions.

MW802 PRO is supplied complete with SE600 combination pH/EC/TDS probe, 20 mL sachet pH 7.01 buffer solution, 20 mL 1413 $\mu\text{S}/\text{cm}$ sachet of calibration solution, 20 mL 1500 ppm sachet of calibration solution, 9V battery and instructions.

- 2 Years warranty
- ATC
- IP65
- 2 Points
- AUTO Buffer
- Dual Display
- Self-Diagnostic
- CE
- Electrode Replacement



pH/EC/TDS/Temp Sensor

The **MW803 MAX** and **MW804 MAX**'s exposed temperature sensor provides fast response time, and its proximity to the conductivity probe guarantees much more accurate temperature compensated readings.



MW803 MAX/MW804 MAX

pH/Conductivity/TDS/Temperature Testers with replaceable electrode

The **MW803 MAX** and **MW804 MAX** are water-resistant testers with dual-level LCD that measure pH/Conductivity/TDS/Temperature in one single tester!

The large display shows readings in an extended range from 0.00 to 14.00 pH and 0 to 3999 $\mu\text{S/cm}$, 0 to 2000 ppm (MW803), 0 to 20.00 mS/cm, 0 to 10.00 ppt (MW804) and simultaneously shows temperature from 0.0 to 50.0°C or 32.0 to 122.0°F. They have a stability indicator and hold function that freezes the display for easy and accurate recording. The large display also has graphic symbols to guide you through all operations. The EC/TDS conversion factor is user selectable as well as the temperature compensation coefficient (β).

Ideal for quick and accurate measurements in swimming pools, aquariums and horticultural applications they can also be used in Industrial and Laboratory applications such as cooling towers, food processing, plating, drinking and waste water etc.

Specifications		 MW803 MAX	 MW804 MAX
Range	pH EC TDS Temp.	0.00 to 14.00 pH 0 to 3999 $\mu\text{S/cm}$ 0 to 2000 ppm 0.0 to 50.0°C / 32.0 to 122.0°F	0.00 to 14.00 pH 0 to 20.00 mS/cm 0 to 10.00 ppt 0.0 to 50.0°C / 32.0 to 122.0°F
Resolution	pH EC TDS Temp.	0.01 pH 1 $\mu\text{S/cm}$ 1 ppm 0.1°C / 0.1°F	0.01 pH 0.01 mS/cm 0.01 ppt 0.1°C / 0.1°F
Accuracy (@25°C)	pH EC/TDS Temp.	± 0.05 pH $\pm 2\%$ Full scale $\pm 0.5^\circ\text{C}$ / $\pm 1^\circ\text{F}$	± 0.05 pH $\pm 2\%$ Full scale $\pm 0.5^\circ\text{C}$ / $\pm 1^\circ\text{F}$
Temperature Compensation		automatic with $\beta=0.0$ to $2.4\%/^\circ\text{C}$	automatic with $\beta=0.0$ to $2.4\%/^\circ\text{C}$
Calibration		automatic, 1 point for EC and 1 or 2 points for pH	automatic, 1 point for EC and 1 or 2 points for pH
TDS Factor		0.45 to 1.00 (conv.)	0.45 to 1.00 (conv.)
Probe		Mi60P (replaceable)	Mi60P (replaceable)
Environment		0 to 50°C; 100% RH max.	0 to 50°C; 100% RH max.
Battery Type		4 x 1.5V; IEC LR44, A76 (included)	4 x 1.5V; IEC LR44, A76 (included)
Battery Life		approx. 100 hours of use	approx. 100 hours of use
Auto-off		after 8 minutes of non-use	after 8 minutes of non-use
Packaging dimensions		254 x 67 x 47 mm	254 x 67 x 47 mm
Packaging weight		220 g	220 g

Accessories

- Mi60P** Replaceable probe for MW803 & MW804
- M10000B** Rinse solution, 20 mL sachet (25 pcs)
- M10004B** pH 4.01 buffer solution 20 mL sachet (25 pcs)
- M10007B** pH 7.01 buffer solution 20 mL sachet (25 pcs)
- M10010B** pH 10.01 buffer solution 20 mL sachet (25 pcs)
- M10016B** Cleaning solution, 20 mL sachet (25 pcs)
- M10030B** 12880 $\mu\text{S/cm}$ calibration solution, 20 mL sachet, 25 pcs
- M10031B** 1413 $\mu\text{S/cm}$ calibration solution, 20 mL sachet, 25 pcs
- M10032B** 1382 ppm (mg/L) calibration solution, 20 mL sachet, (25 pcs)

- M10038B** 6.44 ppt (g/L) calibration solution, 20 mL sachet, (25 pcs)
- MA9004** pH 4.01 buffer solution, 230 mL bottle
- MA9006** pH 6.86 buffer solution, 230 mL bottle
- MA9007** pH 7.01 buffer solution, 230 mL bottle
- MA9009** pH 9.18 buffer solution, 230 mL bottle
- MA9010** pH 10.01 buffer solution, 230 mL bottle
- MA9015** Electrode storage solution, 230 mL
- MA9060** 12880 $\mu\text{S/cm}$ calibration solution, 230 mL bottle
- MA9061** 1413 $\mu\text{S/cm}$ calibration solution, 230 mL bottle
- MA9062** 1382 ppm calibration solution, 230 mL bottle
- MA753** Hard carrying case for 2 testers



Replaceable probe

Replace the probe in a fast and simple way yourself! Just unscrew the plastic ring on the top of the probe and replace the probe with a new one.

Battery life

Percentage of battery power remaining will be displayed upon startup.



Packaging Information

MW803 MAX and **MW804 MAX** is supplied in a carton box. Optionally the MA753 hard carrying case can be purchased.

Ordering Information

MW803 MAX and **MW804 MAX** is supplied complete with protective cap, 20 mL pH 4.01 and pH 7.01 sachets of calibration solution, 20 mL 1413 $\mu\text{S/cm}$ calibration solution (MW803 MAX), 20 mL 12880 $\mu\text{S/cm}$ calibration solution (MW804 MAX), batteries and instructions.



MW700 PRO

Budget LUX Portable Meters for fast and reliable results

The microprocessor-based **MW700 PRO** is a portable Lux meter designed to perform light measurements. **MW700 PRO** has a small, ergonomic and light case design. Other features include large and easy to read LCD and long battery life.

These handy and ergonomically designed portable meters are ideal for anyone working on a low budget and still requires fast and reliable measurements. These portable meters are suitable for a wide range of applications, such as Educational, Agriculture and Horticulture, as well as water and environmental analysis.

Both models are supplied with a light sensor connected to the meter that measures from 0 to 50000 Lux.

Average indoor lighting ranges from 100 to 1000 Lux and average outdoor sun lights about 50000 Lux. Lux is a unit that indicates the density of light that falls on a surface.

The light is necessary for the development of the plants. In fact, it is necessary a sufficient contribution of light in order to favor the photosynthesis and the closing of the plants.

The supplement of light by means of lamps electrical workers is the method simpler and economic in order to bring the necessary light to the plants.

The human eye is sensitive only to blue, green, and red light, so in calculating the Lux falling on an object, only the light that the human eye sees is counted. When only infrared light falls on an object, the Lux is counted as zero since our eyes see nothing. Mathematically, a spectral weighting function becomes convolved with the actual illumination spectrum to calculate Lux exactly.

This is the formal definition of Lux and it makes Lux an unusual unit of measure.

Still, Lux can be thought of as a way of measuring light in terms of what our eyes perceive. The metric unit of measure for luminance of a surface. One Lux is equal to one Lumen per square meter. One Lux equals 0.0929 footcandles.

Range keys

Press one of the three "Range keys" to select the proper scale according to the intensity of the light.



Specifications	MW700 PRO
Range	0.000 to 1999 Lux 2000 to 19999 Lux 20000 to 50000 Lux
Range setting	manual through key buttons
Resolution	1 Lux 10 Lux 100 Lux
Accuracy	±6% of reading ±1 digit
Peak wave length	560 nm
Sensor Type	silicon photodiode
Sensor Sensitivity	100 scotopic Lux
Sensor stability	±2% change per year (in the first two years)
Environment	0 to 50°C / 32 to 122°F; max RH 95%
Battery type	1x9V (IEC 6LR61) alkaline
Battery life	approximately 150 hours of continuous use
Auto-off	after about 5 minutes of non-use
Packaging dimensions	212 x 145 x 67 mm
Packaging weight	400 g

Ordering Information

MW700 PRO is supplied complete with 9V battery and instructions in a carton box.



3 in 1 Combination Photometer!



MI411 PRO

Free & Total Chlorine and pH Photometer

This latest laboratory grade microprocessor photometer has an excellent repeatability and is ideal for field measurements.

Chlorine is the most commonly used water disinfectant. Applications vary from treatment of drinking water and wastewater to pool and spa sanitization and food processing to sterilization.

The **MI411 PRO** is a portable microprocessor based instrument to measure three critical parameters to ensure good water quality: pH, free chlorine and total chlorine.

This instrument provides greater resolution, better accuracy and immediate results.

MI411 PRO is supplied in a hard carrying case including 2 cuvettes, reagents for 100 tests, wiping tissue and instruction manual.

Hard Carrying Case

MI411 PRO comes complete in hard carrying case making it ideal for field measurements.



Specifications		MI411 PRO
Range	Free Chlorine	0.00 to 5.00 mg/L Cl ₂
	Total Chlorine	0.00 to 5.00 mg/L Cl ₂
	pH	6.5 to 8.0 pH
Resolution	Free Chlorine	0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L)
	Total Chlorine	0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L)
	pH	0.1 pH
Accuracy	Free Chlorine	±0.06 mg/L @ 1.50 mg/L
	Total Chlorine	±0.06 mg/L @ 1.50 mg/L
	pH	±0.1 pH @ 7.2 pH
Method	Free Chlorine	adaptation of the USEPA method 330.5 and Standard Method 4500-Cl G
	Total Chlorine	adaptation of the USEPA method 330.5 and Standard Method 4500-Cl G
	pH	adaptation of the phenol red method
Light Source		tungsten lamp
Light Detector		silicon photocell and 525 nm narrow band interference filter
Environment		0 to 50°C / 32 to 122°F; max RH 100%
Battery Type		1 x 9V
Auto-off		after 10 minutes of non use
Packaging dimensions		305 x 280 x 115 mm
Packaging weight		1.26 kg

Accessories

- Mi504-100** Free & Total Chlorine reagent set (100 tests)
- Mi509-100** pH reagent (100 tests)
- Mi511-100** Free & Total Chlorine and pH reagent set (100 tests)
- Mi524-100** Total Chlorine powder reagents (100 tests)
- Mi526-100** Free Chlorine powder reagents (100 tests)

- Mi0001** Glass cuvettes (2 pcs)
- Mi0002** Caps for cuvettes (2 pcs)
- Mi0003** Stoppers for cuvettes (2 pcs)



Ordering Information

MI411 PRO is supplied complete with 2 cuvettes, Mi511-100 liquid reagents for 100 tests, hard carrying case, wiping tissue, 9V battery and instructions.

MI405 PRO/MI407 PRO/MI408 PRO/MI412 PRO Ammonia, Iron & Phosphate Photometers

These user-friendly Colorimeters will give you direct readings in mg/L.

Ammonia detection in water treatment systems is particularly important for aquarium owners and fish farm operators.

Ammonia is highly soluble in water and extremely toxic to fish. Fish farm owners must monitor and maintain careful control of ammonia levels to ensure optimum water conditions for their stock.

Milwaukee offers 2 instruments for low and medium concentrations: **MI405 PRO** with a range of 0.00 to 9.99 mg/L and **MI407 PRO** from 0.00 to 3.00 mg/L.

Iron is naturally present in water supplies and its presence in both potable and industrial applications is regarded as objectionable. Milwaukee offers **MI408 PRO** Iron meter with a range of 0.00 to 5.00 mg/L.

Phosphates are present in natural waters and at concentrations typically found, do not pose any specific health threats to humans.

However, excessive contamination of water courses from agricultural fertilizer run off or wastewater/effluent discharge can promote excessive algae or plant growth. Milwaukee offers **MI412 PRO** with range 0.00 to 2.50 mg/L.



Specifications		 MI405 PRO Ammonia MR	 MI407 PRO Ammonia LR	 MI408 PRO Iron HR	 MI412 PRO Phosphate LR
Range	Ammonia Iron Phosphate	0.00 to 9.99 mg/L (NH ₃ -N)	0.00 to 3.00 mg/L (NH ₃ -N)	0.00 to 5.00 mg/L (Fe)	0.00 to 2.50 mg/L (PO ₄)
Resolution	Ammonia Iron Phosphate	0.01 mg/L	0.01 mg/L	0.01 mg/L	0.01 mg/L
Accuracy	Ammonia Iron Phosphate	±0.30 mg/L @5.00 mg/L	±0.09 mg/L @1.50 mg/L	±0.06 mg/L @1.50 mg/L	±0.07 mg/L @1.00 mg/L
Method		adaptation of Nessler method	adaptation of Nessler method	adaptation of the USEPA method 315 B and Standard method 3500 - Fe B	adaptation of the Ascorbic Acid method
Light Source		Blue LED 466 nm	Blue LED 466 nm	tungsten lamp	tungsten lamp
Light Detector		silicon photocell and 466 nm narrow band interference filter	silicon photocell and 466 nm narrow band interference filter	silicon photocell and 525 nm narrow band interference filter	silicon photocell and 610 nm narrow band interference filter
Environment		0 to 50°C / 32 to 122°F max RH 100%	0 to 50°C / 32 to 122°F max RH 100%	0 to 50°C / 32 to 122°F max RH 100%	0 to 50°C / 32 to 122°F max RH 100%
Battery Type		1 x 9 V	1 x 9 V	1 x 9 V	1 x 9 V
Auto-off		after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use
Packaging dimensions		305 x 280 x 115 mm	305 x 280 x 115 mm	305 x 280 x 115 mm	305 x 280 x 115 mm
Packaging weight		1.24 kg	1.22 kg	1.22 kg	1.3 kg

Accessories

- Mi505-100** Ammonia MR liquid reagent (100 tests)
- Mi507-100** Ammonia LR liquid reagent (100 tests)
- Mi508-100** Iron HR liquid reagent (100 tests)
- Mi512-100** Phosphate LR powder reagent (100 tests)

- Mi0001** Glass cuvetts (2 pcs)
- Mi0002** Caps for cuvetts (2 pcs)
- Mi0003** Stoppers for cuvetts (2 pcs)



Ordering Information

MI405 PRO, **MI407 PRO**, **MI408 PRO** and **MI412 PRO** are supplied complete with 2 cuvetts, reagents for 100 tests, hard carrying case, wiping tissue, 9V battery and instructions.



MI404 PRO/MI406 PRO/MI413 PRO/MI414 PRO

Free & Total Chlorine and Chloride Photometers



Milwaukee provides a range of chlorine photometers for all applications: swimming pool treatments, household cleaners, dishwasher additives, laundry powders/liquids and cooling water treatment products all contain chlorine as an oxidizing biocide. Drinking water contains residual chlorine to maintain water purity throughout the supply lines.

Milwaukee offers 3 microprocessor-based instruments with greater resolution, better accuracy and immediate results. You can choose between three different models: **MI404 PRO** for measuring free (0.00 to 5.00 mg/L) and total (0.00 to 5.00 mg/L) chlorine, **MI406 PRO** for measuring free (0.00 to 5.00 mg/L) chlorine and **MI413 PRO** for measuring free (0.00 to 10.00 mg/L) and total (0.00 to 10.00 mg/L) chlorine.



Chloride is a major constituent of sea water and is extremely corrosive in acidic environments. It requires close monitoring in applications such as marine boiler systems that are effected by seawater contamination. Chlorides are used by the water treatment professional to determine cycles of concentration in low pressure boilers and cooling systems. It is essential to monitor chloride concentrations in boiler systems to prevent metal parts being damaged. In high levels, chloride can corrode stainless steel. Milwaukee offers the **MI414 PRO** microprocessor-based photometer for measuring chloride (0.00 to 20.00 mg/L).

Specifications		 MI404 PRO Free & Total Chlorine	 MI406 PRO Free Chlorine	 MI413 PRO Free & Total Chlorine HR	 MI414 PRO Chloride
Range	Free Chlorine Total Chlorine Chloride	0.00 to 5.00 mg/L (Cl ₂) 0.00 to 5.00 mg/L (Cl ₂)	0.00 to 5.00 mg/L (Cl ₂)	0.00 to 10.00 mg/L (Cl ₂) 0.00 to 10.00 mg/L (Cl ₂)	0.00 to 20.00 mg/L (Cl ⁻)
Resolution	Free Chlorine Total Chlorine Chloride	0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L); 0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L)	0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L)	0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L); 0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L)	0.01 mg/L
Accuracy	Free Chlorine Total Chlorine Chloride	±0.06 mg/L @1.50 mg/L ±0.06 mg/L @1.50 mg/L	±0.06 mg/L @1.50 mg/L	±0.17 mg/L @1.50 mg/L ±0.17 mg/L @1.50 mg/L	±1.0 mg/L @10.0 mg/L
Method		adaptation of USEPA method 330.5 and Standard Method 4500-Cl G	adaptation of USEPA method 330.5 and Standard Method 4500-Cl G	adaptation of USEPA method 330.5 and Standard Method 4500-Cl G	adaptation of mercury (II) thiocyanate method
Light Source		tungsten lamp	tungsten lamp	tungsten lamp	Blue LED 466 nm
Light Detector		silicon photocell and 525 nm narrow band interference filter	silicon photocell and 525 nm narrow band interference filter	silicon photocell and 525 nm narrow band interference filter	silicon photocell and 466 nm narrow band interference filter
Environment		0 to 50°C / 32 to 122°F max RH 100%	0 to 50°C / 32 to 122°F max RH 100%	0 to 50°C / 32 to 122°F max RH 100%	0 to 50°C / 32 to 122°F max RH 100%
Battery Type		1 x 9 V	1 x 9 V	1 x 9 V	1 x 9 V
Auto-off		after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use
Packaging dimensions		305 x 280 x 115 mm	305 x 280 x 115 mm	305 x 280 x 115 mm	305 x 280 x 115 mm
Packaging weight		1.24 kg	1.26 kg	1.52 kg	1.44 kg

Accessories

- Mi504-100** Free & Total Chlorine liquid reagent set (100 tests)
- Mi506-100** Free Chlorine liquid reagent set (100 tests)
- Mi513-045** Free & Total Chlorine liquid reagent set (45 tests)
- Mi514-100** Chloride liquid reagent set (100 tests)



- Mi524-100** Total Chlorine powder reagents (100 tests)
- Mi526-100** Free Chlorine powder reagents (100 tests)
- Mi0001** Glass cuvettes (2 pcs)
- Mi0002** Caps for cuvettes (2 pcs)
- Mi0003** Stoppers for cuvettes (2 pcs)

Ordering Information

MI404 PRO, MI406 PRO, MI413 PRO and **MI414 PRO** are supplied complete with 2 cuvettes, reagents, hard carrying case, wiping tissue, 9V battery and instructions.

MW10/MW11

Low cost digital photometers to measure Free & Total Chlorine

Chlorine is the most commonly used water disinfectant. Applications vary from treatment of drinking water and wastewater to pool and spa sanitization and food processing to sterilization.

Milwaukee offers 2 models:

MW10 for measuring free chlorine (0.00 to 2.50 mg/L)

MW11 to measure total chlorine (0.00 to 3.50 mg/L).

Key features include:

- User friendly;
- Small & Ergonomic case design;
- Inexpensive;
- Large and easy to read display;
- Good accuracy and immediate results;



- 2 Years warranty
- Self diagnostics
- LED
- CE

Specifications	MW10 Free chlorine	MW11 Total chlorine
Range	0.00 to 2.50 ppm	0.00 to 3.50 ppm
Resolution	0.01 ppm	0.01 ppm
Accuracy (@25°C)	±0.03 ppm ±3% of reading	±0.03 ppm ±3% of reading
Typical EMC Dev.	±0.01 ppm	±0.01 ppm
Light Source	Light Emitting Diode @ 525 nm	Light Emitting Diode @ 525 nm
Light Detector	Silicon Photocell	Silicon Photocell
Method	Adaptation of USEPA method 330.5. The reaction between free chlorine and the DPD reagent causes a pink tint in the sample.	Adaptation of USEPA method 330.5. The reaction between free chlorine and the DPD reagent causes a pink tint in the sample.
Environment	0 to 50°C (32 to 122°F) max. 95% RH non-condensing	0 to 50°C (32 to 122°F) max. 95% RH non-condensing
Battery Type	1 x 1.5V AAA	1 x 1.5V AAA
Auto-off	after 2 minutes of non use	after 2 minutes of non use
Packaging dimensions	115 x 115 x 84 mm	115 x 115 x 84 mm
Packaging weight	180 g	180 g



The handy photometers are supplied in a carton box including all accessories.

Accessories

- Mi526-25** Free Chlorine powder reagent, (25 pcs)
- Mi524-25** Total Chlorine powder reagent (25 pcs)



- Mi0011** Glass cuvetts (2 pcs)
- Mi0013** Stoppers for cuvetts (2 pcs)

Ordering information:

All handy photometers are supplied in a carton box including 2 cuvetts, 6 powder reagents, 1 x 1.5 V AAA battery and instructions.

- 2 Years warranty
- Self diagnostic
- LED
- CE



MW12/MW13/MW14

Low cost digital photometers to measure Phosphate, Iron & Iodine

Iron is naturally present in water supplies and therefore needs to be monitored both in potable and industrial applications. Milwaukee offers the **MW14** Iron meter with a range of 0.00 to 5.00 mg/L.

Phosphates are present in natural waters and at concentrations typically found, do not pose any specific health threats to humans. However, excessive contamination of water courses from agricultural fertilizer run off or wastewater / effluent discharge can promote excessive algae or plant growth. Milwaukee offers **MW12** with a range of 0.00 to 2.50 mg/L.

Iodine is used as disinfectant in various applications - one of the most common is the poultry industry waste water treatment. Milwaukee offers **MW13** with a range of 0.0 to 12.5 mg/L.

Specifications	MW12 Phosphate	MW13 Iodine	MW14 Iron
Range	0.00 to 2.50 ppm	0.0 to 12.5 ppm	0.00 to 5.00 ppm
Resolution	0.01 ppm	0.1 ppm	0.01 ppm
Accuracy (@25°C)	±0.04 ppm ±4% of reading	±0.1 ppm ±5% of reading	±0.04 ppm ±2% of reading
Typical EMC Dev.	±0.01 ppm	±0.1 ppm	±0.01 ppm
Light Source	LED @ 525 nm	LED @ 525 nm	LED @ 525 nm
Light Detector	Silicon Photocell	Silicon Photocell	Silicon Photocell
Method	Adaptation of the Standard Methods for the Examination of Water and Wastewater, 20th edition, Ascorbic Acid method. The reaction between phosphate and the reagent causes a blue tint in the sample.	Adaptation of the Standard Methods for the Examination of Water and Wastewater, 18th edition, DPD method. The reaction between iodine and the reagent causes a pink tint in the sample.	Adaptation of the EPA Phenantroline method 315B, for natural and treated waters. The reaction between iron and reagent causes an orange tint in the sample.
Environment	0 to 50°C (32 to 122°F) max 95% RH non-condensing	0 to 50°C (32 to 122°F) max 95% RH non-condensing	0 to 50°C (32 to 122°F) max 95% RH non-condensing
Battery Type	1 x 1.5V AAA	1 x 1.5V AAA	1 x 1.5V AAA
Auto-off	after 2 minutes of non use	after 2 minutes of non use	after 2 minutes of non use
Packaging dimensions	115 x 115 x 84 mm	115 x 115 x 84 mm	115 x 115 x 84 mm
Packaging weight	180 g	180 g	180 g

Accessories

- Mi512-25** Phosphate powder reagent (25 pcs)
- Mi527-25** Iodine powder reagent (25 pcs)
- Mi528-25** Iron powder reagent (25 pcs)



- Mi0011** Glass cuvettes (2 pcs)
- Mi0013** Stoppers for cuvettes (2 pcs)

Ordering information:

All handy photometers are supplied in a carton box including 2 cuvettes, 6 powder reagents, 1 x 1.5 V AAA battery and instructions.



MI490

Peroxide Value Photometer for Edible Oils

MI490 is a user-friendly photometer for monitoring peroxide value in the process of oil making. This instrument will give you direct readings, with a range of 0.0 to 25.0 meq O₂/Kg .

The measurement of the oil's chemical degradation is the peroxide value, which measures the degree to which the oil is oxidized. Rancidification is the decomposition of fats and other lipids by hydrolysis and/or oxidation. Hydrolysis will split fatty acid chains away from the glycerol backbone in glycerides. These free fatty acids can then undergo further auto-oxidation. Oxidation primarily occurs with unsaturated fats by a free radical-mediated process.

One of the most widely used tests for oxidative rancidity, peroxide value is a measure of the concentration of peroxides and hydroperoxides formed in the initial stages of lipid oxidation. Milliequivalents of peroxide per kg of fat are measured by titration with iodide ion.

Peroxide values are not static and care must be taken in handling and testing samples. It is difficult to provide a specific guideline relating peroxide value to rancidity. High peroxide values are a definite indication of a rancid fat, but moderate values may be the result of depletion of peroxides after reaching high concentrations.

Easy Steps

Prepare the sample with oil and the reagent then insert it in the instrument and note the reading.

Accurate Readings

MI490 will give you direct readings, with a range of 0.0 to 25.0 meq O₂/Kg in the process of oil making.



Specifications	MI490 Peroxide Value
Range	0.0 to 25.0 meq O ₂ /Kg
Resolution	0.5 meq O ₂ /Kg
Accuracy	±0.5 meq O ₂ /Kg
Method	adaptation of the CE n. 2568/97 method
Environment	0 to 50°C; max RH 95%
Battery Type	4 x 1.5V AA
Auto-off	after 15 minutes of non-use
Packaging dimensions	340 x 260 x 118 mm
Packaging weight	1.76 kg



Accessories

MI590-021 Peroxides reagent set (21 tests)



Ordering Information

MI490 is supplied complete with: reagents for 20 tests, 4 x 1 mL syringe, tissue for wiping cuvetts, 4 x 1.5V AA batteries and instruction manual.

MI415 PRO Turbidity Meter



Turbidity refers to the concentration of undissolved, suspended particles present in a liquid. Turbidity is a measure of the clarity of a sample. For potable water applications turbidity is a good indicator of water quality.

Turbidity Measurement is achieved by analyzing the amount of light refracted from suspended particles such as clay, silt and organic material.

By measuring turbidity, by photometric or tube methods, it is possible to estimate suspended solids content.

MI415 PRO has two operating ranges; 0.00 to 50.00 FNU, and 50 to 1000 FNU that can accommodate the most turbid condition you may encounter.

MI415 PRO is supplied in a hard carrying case, complete with all accessories.



Specifications	MI415 PRO Turbidity meter
Range	0.00 to 50.00 FNU; 50 to 1000 FNU
Resolution	0.01 FNU; 1 FNU
Accuracy	±0.5 FNU or ±5% of reading, whichever is greater
Method	detection of scattered light
Light Source	high emission infrared LED
Light Detector	silicon photocell
Environment	0 to 50°C 32 to 122°F; max RH 100%
Battery Type	1 x 9V
Auto-off	after 5 minutes of non-use
Packaging dimensions	305 x 280 x 115 mm
Packaging weight	1.24 kg

Introduction to Turbidity

The cloudy appearance of water (called Turbidity) is caused by suspended material. The unit of measure adopted by the ISO Standard is the FNU (Formazine Nephelometric Unit) and by EPA is NTU (Nephelometric Turbidity Unit).

The other two methods used to test for turbidity and their measurement units are the JTU (Jackson Turbidity Unit) and the Silica unit (mg/L SiO₂).

See the conversion table of these methods and their units for your reference.

(mg/L)	JTU	FTU (NTU/FNU)	SiO ₂
JTU	1	19	2.5
FTU	0.053	1	0.13
SiO ₂	0.4	7.5	1

Accessories

Mi515-100 AMCO-AEPA-1 @ 0 FNU calibration solution, 30 mL
 AMCO-AEPA-1 @ 10 FNU, calibration solution, 30 mL
 AMCO-AEPA-1 @ 500 FNU, calibration solution, 30 mL



Mi0011 Glass cuvettes (2 pcs)
Mi0012 Caps for cuvettes (2 pcs)
Mi0013 Stoppers for cuvettes (2 pcs)

Ordering Information

MI415 PRO is supplied complete with 2 cuvettes, calibration solutions, hard carrying case, wiping tissue, 9V battery and instructions.

MA871/MA872/MA873/MA881 Digital Refractometers for Brix, Fructose, Glucose and Invert Sugar Measurements

The digital refractometers are optical instruments that employ the measurement of refractive index to determine the % Brix of sugar (MA871), % Fructose (MA872), % Glucose (MA873) and % Invert Sugar (MA881) in aqueous solutions.

The method is both simple and quick. Samples are measured after a simple user calibration with deionized or distilled water. Within seconds the instruments measure the refractive index of the sample and convert it to % Brix or % by weight concentration units.

The digital refractometers eliminate the uncertainty associated with mechanical refractometers and are easily portable for measurements in the field.

The measurement technique and temperature compensation employ methodology recommended in the ICUMSA Methods Book (Internationally recognized body for Sugar Analysis). Temperature (in °C or °F) is displayed simultaneously with the measurement on the large dual level display along with icons for Low Power and other helpful message codes.



Key features include:

- Dual-level LCD
- Automatic Temperature Compensation (ATC)
- Easy setup and storage
- Battery operation with Low Power indicator (BEPS)
- Automatically turns off after 3 minutes of non-use

Specifications	 MA871 Brix	 MA872 Fructose	 MA873 Glucose	 MA881 Invert Sugar
Range	0 to 85% Brix 0 to 80°C / 32 to 176°F	0 to 85% mass 0 to 80°C / 32 to 176°F	0 to 85% mass 0 to 80°C / 32 to 176°F	0 to 85% mass 0 to 80°C / 32 to 176°F
Resolution	0.1% Brix 0.1°C / 0.1°F	0.1% 0.1°C / 0.1°F	0.1% 0.1°C / 0.1°F	0.1% 0.1°C / 0.1°F
Accuracy	±0.2% Brix ±0.3°C / ±0.5°F	±0.2% ±0.3°C / ±0.5°F	±0.2% ±0.3°C / ±0.5°F	±0.2% ±0.3°C / ±0.5°F
Light source	yellow LED	yellow LED	yellow LED	yellow LED
Measurement Time	approximately 1.5 seconds	approximately 1.5 seconds	approximately 1.5 seconds	approximately 1.5 seconds
Minimum Sample Volume	100 µL (cover prism totally)	100 µL (cover prism totally)	100 µL (cover prism totally)	100 µL (cover prism totally)
Sample Cell	SS ring and flint glass prism	SS ring and flint glass prism	SS ring and flint glass prism	SS ring and flint glass prism
Temperature Compensation	automatic between 10 and 40°C / 50 to 104°F	automatic between 10 and 40°C / 50 to 104°F	automatic between 10 and 40°C / 50 to 104°F	automatic between 10 and 40°C / 50 to 104°F
Case Material	ABS	ABS	ABS	ABS
Battery Type	1 x 9V AA (included)	1 x 9V AA (included)	1 x 9V AA (included)	1 x 9V AA (included)
Battery Life	5000 reading	5000 reading	5000 reading	5000 reading
Auto-shut off	after 3 minutes of non-use	after 3 minutes of non-use	after 3 minutes of non-use	after 3 minutes of non-use
Packaging dimensions	268 x 122 x 118 mm	268 x 122 x 118 mm	268 x 122 x 118 mm	268 x 122 x 118 mm
Packaging weight	660 g	660 g	660 g	660 g

Ordering Information

MA871, MA872, MA873 and MA881 are supplied in a carton box, complete with 9V battery, pipette and instruction manual. Optionally you can also order the refractometers in a hard carrying case (MA752).

Stainless Steel Sample Well and Prism

Place a few drops of the sample in the well and press the READ key.





MA882/MA883/MA884/MA885 Digital Refractometers for Grape Juice Must Measurements

The **MA882**, **MA883**, **MA884** and **MA885** are optical instruments that are based on the measurement of the refractive index of a solution. The measurement of refractive index is simple and quick and provides the vintner an accepted method for sugar content analysis. Samples are measured after a simple user calibration with deionized or distilled water. Within seconds the instrument measures the refractive index of the grape. This digital refractometers eliminate the uncertainty associated with mechanical refractometers and are easily portable for measurements in the field.





The four instruments utilize internationally recognized references for unit conversion and temperature compensation.

Temperature (in °C or °F) is displayed simultaneously with the measurement on the large dual level display along with icons for Low Power and other helpful message codes.

Key features include:

- Dual-level LCD
- Easy setup and storage
- Automatic Temperature Compensation (ATC)
- Battery operation with Low Power indicator (BEPS)
- Automatically turns off after 3 minutes of non-use

- **MA882** measures %Brix;
- **MA883** measures °Baumé;
- **MA884** measures %Brix and Potential Alcohol (% vol);
- **MA885** measures %Brix, °Oechsle (°Oe) and °KMW (°Babo).

Specifications	 MA882	 MA883	 MA884	 MA885
Range	0 to 50% Brix 0 to 80°C / 32 to 176°F	0 to 28 °Baumé 0 to 80°C / 32 to 176°F	0 to 50% Brix 0 to 25% v/v Potential Alc. 0 to 80°C / 32 to 176°F	0 to 50% Brix 0 to 230 °Oechsle 0 to 42 °KMW 0 to 80°C / 32 to 176°F
Resolution	0.1% Brix 0.1°C / 0.1°F	0.1 °Baumé 0.1°C / 0.1°F	0.1% Brix 0.1% v/v Potential Alcohol 0.1°C / 0.1°F	0.1% Brix 0.1 °Oechsle 0.1 °KMW 0.1°C / 0.1°F
Accuracy	±0.2% Brix ±0.3°C / ±0.5°F	±0.1 °Baumé ±0.3°C / ±0.5°F	±0.2% Brix ±0.2 v/v Potential Alcohol ±0.3°C / ±0.5°F	±0.2% Brix ±1 °Oechsle ±0.2 °KMW ±0.3°C / ±0.5°F
Light Source	yellow LED	yellow LED	yellow LED	yellow LED
Measurement Time	approximately 1.5 seconds	approximately 1.5 seconds	approximately 1.5 seconds	approximately 1.5 seconds
Minimum Sample Volume	100 µL (cover prism totally)	100 µL (cover prism totally)	100 µL (cover prism totally)	100 µL (cover prism totally)
Sample Cell	SS ring and flint glass prism	SS ring and flint glass prism	SS ring and flint glass prism	SS ring and flint glass prism
Temperature Compensation	automatic between 10 and 40°C / 50 to 104°F	automatic between 10 and 40°C / 50 to 104°F	automatic between 10 and 40°C / 50 to 104°F	automatic between 10 and 40°C / 50 to 104°F
Case Material	ABS	ABS	ABS	ABS
Battery Type	1 x 9V AA (included)	1 x 9V AA (included)	1 x 9V AA (included)	1 x 9V AA (included)
Battery Life	5000 reading	5000 reading	5000 reading	5000 reading
Auto-shut off	after 3 minutes of non-use	after 3 minutes of non-use	after 3 minutes of non-use	after 3 minutes of non-use
Packaging dimensions	268 x 122 x 118 mm	268 x 122 x 118 mm	268 x 122 x 118 mm	268 x 122 x 118 mm
Packaging weight	660 g	660 g	660 g	660 g

Ordering Information

MA882, **MA883**, **MA884** and **MA885** are supplied in a carton box, complete with 9V battery, pipette and instruction manual.

Optionally you can also order the refractometers in a hard carrying case (**MA752**).



MA886 Digital Refractometer for Sodium Chloride Measurements


The **MA886** is an optical instrument that employs the measurement of the refractive index to determine sodium chloride concentration in aqueous solutions used in food preparation.

It is not intended for sea water salinity measurements.

The measurement of refractive index is simple and quick and provides the user an accepted method for NaCl analysis. Samples are measured after a simple user calibration with deionized or distilled water. Within seconds the instrument measures the refractive index of the solution.

The digital refractometer eliminates the uncertainty associated with mechanical refractometers and is easily portable for measurements where you need them.

The instrument utilizes internationally recognized references for unit conversion and temperature compensation. It can display the measurement of NaCl concentration 4 different ways: g/100 g, g/100 mL, Specific Gravity, and °Baumé. Temperature (in °C or °F) is displayed simultaneously with the measurement (on 3 of the ranges) on the large dual level display along with icons for Low Power and other helpful message codes.



Key features include:

- Dual-level LCD
- Automatic Temperature Compensation (ATC)
- Easy setup and storage
- Battery operation with Low Power indicator (BEPS)
- Automatically turns off after 3 minutes of non-use

Specifications	MA886
Range	0 to 28 g/100 g 0 to 34 g/100 ml 1.000 to 1.216 Specific Gravity 0 to 26 °Baumé 0 to 80°C / 32 to 176°F
Resolution	0.1 g/100 g 0.1 g/100 ml 0.001 Specific Gravity 0.1 °Baumé 0.1°C / 0.1°F
Accuracy	±0.2 g/100 g ±0.2 g/100 ml ±0.002 Specific Gravity ±0.2 °Baumé ±0.3°C / ±0.5°F
Light Source	yellow LED
Measurement Time	approximately 1.5 seconds
Minimum Sample Volume	100 µL (cover prism totally)
Sample Cell	SS ring and flint glass prism
Temperature Compensation	automatic between 10 and 40°C (50 to 104°F)
Case Material	ABS
Battery Type	1 x 9V AA (included)
Battery Life	5000 reading
Auto-shut off	after 3 minutes of non-use
Packaging dimensions	268 x 122 x 118 mm
Packaging weight	660 g



Stainless Steel Sample Well and Prism

Place a few drops of the sample in the well and press the READ key.

Liquid Crystal Display (LCD)

Dual Level LCD with Primary and Secondary Display.



Ordering Information

MA886 is supplied in a carton box, complete with 9V battery, pipette and instruction manual. Optionally you can also order the refractometers in a hard carrying case (**MA752**).



Measuring salt in cheese Using MA886 Digital Sodium Chloride Refractometer

Sodium occurs naturally in many foods and is also added in the form of salt. The sodium content of food has important implications for health. Sodium is a nutrient and is part of the group of dietary minerals. Essential to life, it cannot be produced by the human body and thus has to be provided by the diet. The physiological requirements of sodium of the human body are relatively low (estimated at the equivalent of 1 to 2 gram of salt per day) and are met by the diet.



Fresh cheeses (non-salted) contain very little sodium (from 30 to 60 mg /100g). Hard cheeses – because of added salt – contain much higher levels of sodium (from 200 to 1600 mg/100g). Within a family of cheeses and depending on the brands, large variations exist between sodium contents of the cheeses, depending on lower or higher addition of salt by the cheese maker.

Measuring salt (sodium chloride) in cheese



1. Dicing:
Mincing the sample increases the surface area to allow as much salt to be released into the water as possible.



2. Dilution:
Dilute the sample with hot water to a 10% ratio.
After the sample melted, the fat will float to the top.


3. Collect the sample with a pipette from the layer underneath the fat



4. Using the plastic pipette, drip sample onto the prism surface. Fill the well completely.

5. Press the READ key.
The results are displayed in unit of interest

For optimal measurement put a sample into a beaker.



MA887 Digital Refractometer for Seawater Measurements

The **MA887** is an optical instrument that employs the measurement of the refractive index to determine the salinity of natural and artificial seawater, ocean water or brackish intermediates. The digital refractometer eliminates the uncertainty associated with mechanical refractometers and is easily portable for ship, shore or home use.

The **MA887** refractometer is an optical device that is simple and quick to use. Samples are measured after a simple user calibration with distilled or deionized water. Within seconds, the refractive index and temperature are measured and converted into one of three popular measurement units; Practical Salinity Units (PSU), Salinity in parts per thousand (ppt), or Specific Gravity (S.G. (20/20)).

All conversion algorithms are based upon respected scientific publications using the physical properties of seawater (not sodium chloride). The temperature (in °C or °F) is also displayed on the large dual level display along with helpful message codes.



- 2 Year warranty
- ATC
- Dual Display
- Self Diagnostics
- CE

Key features include:

- Dual-level LCD
- Automatic Temperature Compensation (ATC)
- Easy setup and storage
- Battery operation with Low Power indicator (BEPS)
- Automatically turns off after 3 minutes of non-use

Specifications	MA887
Range	0 to 50 PSU 0 to 150 ppt 1.000 to 1.114 S.G. (20/20) 0 to 80°C / 32 to 176°F
Resolution	1 PSU 1 ppt 0.001 S.G. (20/20) 0.1°C / 0.1°F
Accuracy	±2 PSU ±2 ppt ±0.002 S.G. (20/20) ±0.3°C / 0.5°F
Light Source	yellow LED
Measurement Time	approximately 1.5 seconds
Minimum Sample Volume	100 µL (cover prism totally)
Sample Cell	SS ring and flint glass prism
Temperature Compensation	automatic between 10 and 40°C (50 to 104°F)
Case Material	ABS
Battery Type	1 x 9V AA (included)
Battery Life	5000 reading
Auto-shut off	after 3 minutes of non-use
Packaging dimensions	268 x 122 x 118 mm
Packing weight	660 g



Stainless Steel Sample Well and Prism

Place a few drops of the sample in the well and press the READ key.

Liquid Crystal Display (LCD)

Dual Level LCD with Primary and Secondary Display.



Ordering Information

MA887 is supplied in a carton box, complete with 9V battery, pipette and instruction manual. Optionally you can also order the refractometers in a hard carrying case (**MA752**).



MA888

Digital Refractometer for Ethylene Glycol Measurements

The **MA888** is an optical instrument that employs the measurement of the refractive index to determine the % volume and freezing point of ethylene glycol based coolants or antifreeze.

The digital refractometer eliminates the uncertainty associated with mechanical refractometers and is easily portable for use in the field to optimize your cooling system.

The **MA888** refractometer is an optical device that is simple and quick to use. Samples are measured after a simple user calibration with distilled or deionized water. Within seconds, the refractive index and temperature are measured and converted into one of two measurement units; % Volume or Freezing Point.

The instrument utilizes internationally recognized references for unit conversion and temperature compensation for ethylene glycol solutions (e.g. CRC Handbook of Chemistry and Physics, 87th Edition).

The temperature (in °C or °F) is also displayed on the large dual level display along with helpful message codes.

Key features include:

- Dual-level LCD
- Automatic Temperature Compensation (ATC)
- Easy setup and storage
- Battery operation with Low Power indicator (BEPS)
- Automatically turns off after 3 minutes of non-use



Specifications	MA888
Range	0 to 100% Volume 0 to -50°C / 32 to -58°F Freezing Point 0 to 80°C / 32 to 176°F
Resolution	0.1% Volume 0.1°C / 0.1°F Freezing Point 0.1°C / 0.1°F
Accuracy	±0.2% Volume ±0.5°C / ±1.0°F Freezing Point ±0.3°C / ±0.5°F
Light Source	yellow LED
Measurement Time	approximately 1.5 seconds
Minimum Sample Volume	100 µL (cover prism totally)
Sample Cell	SS ring and flint glass prism
Temperature Compensation	automatic between 10 and 40°C (50 to 104°F)
Case Material	ABS
Battery Type	1 x 9V AA (included)
Battery Life	5000 reading
Auto-shut off	after 3 minutes of non-use
Packaging dimensions	268 x 122 x 118 mm
Packaging weight	660 g



Stainless Steel Sample Well and Prism

Place a few drops of the sample in the well and press the READ key.

Liquid Crystal Display (LCD)

Dual Level LCD with Primary and Secondary Display.



Ordering Information

MA888 is supplied in a carton box, complete with 9V battery, pipette and instruction manual. Optionally you can also order the refractometers in a hard carrying case (**MA752**).



TH300/TH310

Pocket-sized thermometers with automatic calibration check

Scientists and laboratory technicians rely on the accuracy of their thermometers when performing routine measurements. For this reason, Milwaukee developed the **TH310**. This palm-sized unit is a highly accurate thermometer that is destined to make glass thermometers obsolete.

Remote temperature measurements require a versatile thermometer with a remote probe that can be used in a hard-to-reach places. The meter must also be easily readable at an angle. The **TH300** is equipped with a stainless steel general purpose probe and 1 meter cable to make remote reading a simple task.

The thermometers have easy-to-read display which shows clear readings at any angle.

Specifications	TH300	TH310
Range	-50.0 to 150.0°C	-50.0 to 150.0°C
Resolution	0.1°C	0.1°C
Accuracy (@20°C)	±0.5°C (-20 to 90°C)	±0.5°C (-20 to 90°C)
Typical EMC Deviation	±0.3°C	±0.3°C
Probe	Stainless steel with 1 meter cable	Stainless steel
Switch ON/OFF	no	yes
Calibration Check	no	yes
Environment	0 to 50°C; max RH 95%	0 to 50°C; max RH 95%
Battery Type	1 x 1.4V	1 x 1.5V
Battery Life	approximately 1 year	approximately 3000 hours of continuous use
Packaging dimensions	225 x 91 x 47 mm	254 x 67 x 47 mm
Packaging weight	140 g	100 g



Ordering Information

TH300 is supplied with stainless steel probe with 1 meter cable, batteries and instruction manual.

TH310 is supplied with batteries and instruction manual.

MT6003

NPK Soil Test Kit

The primary nutrients essential to plant growth and quality are Nitrogen, Phosphorous and Potassium.

N is associated with plant growth above the ground, **P** is responsible for flower and fruit production as well as overall plant health. **K** helps disease resistance, water intake and strong root growth.

This kit provides accurate and professional tests and includes 25 sachets of Nitrogen (MT5009), Phosphorous (MT5010) and Potassium (MT5002), 3 x 100 mL bottles of extraction solution and 5 plastic test tubes. All results are compared to standards on laminated colour charts.



Mi455 PRO

Mini-titrator for the determination of FREE & TOTAL SULPHUR DIOXIDE in wine analysis



Mi455 PRO is a user-friendly microprocessor-based mini-titrator for the determination of free and total sulphur dioxide in the process of wine making. This mini-titrator will give you direct readings with a range of 0 to 400 ppm.

The instrument comes with a pre-programmed analysis method for free and total sulphur dioxide measurements on wine sample.

Specifications	Mi455 PRO Sulphur Dioxide
Range	0 to 400 ppm of SO ₂
Resolution	1 ppm
Accuracy	5% of reading
Method	ripper titrimetric method
Principle	equivalence point redox titration
Sample volume	50 mL
ORP electrode	MA924B/1 (included)
Pump debit	0.5 mL/min
Stirring speed	1500 rpm
Environment	0 to 50°C; max RH 95%
Power supply	220V/50 Hz; 10VA
Dimensions	350 x 310 x 250 mm
Weight	5,5 kg

Ordering Information

Mi455 PRO is supplied complete with: Calibration standard SO₂, Titrant SO₂, Alkaline reagent for total SO₂, Acid reagent for total SO₂, Acid reagent for free SO₂, Stabilizer, SO₂, MA924B/1 ORP electrode, small stir bar, 2 x 50 mL beakers, 2 x 25 mL beakers, Refilling Electrolyte Solution 3.5M KCl for ORP electrodes 230 mL bottle, test tube set, O-ring, 1 mL syringe, power cable and instruction manual.

Mi 456 PRO Mini-titrator for the determination of TITRATABLE TOTAL ACIDITY for wine analysis

Mi456 PRO is a user-friendly microprocessor-based mini-titrator for the determination of the titratable total acidity in the process of wine making. This minititrator gives you direct readings in g/L of tartaric acid, with a range of 0.0 to 25.0 g/L.

The instrument comes with a pre-programmed analysis method for the titratable total acidity measurements on wine sample.



Specifications	Mi456 PRO Titratable Total Acidity
Range	0.0 to 25.0 g/L of tartaric acid
Resolution	0.1 g/L
Accuracy	5% of reading
Method	acid-base titration method
Principle	end-point titration
pH Calibration	1 point in selected end-point: 7.00 pH or 8.20 pH
Sample volume	2 mL
Temperature Compensation	Automatic from 0.0 to 100.0°C
pH Electrode	MA919B/1 (included)
Temperature Probe	MA831R (included)
Pump debit	0.5 mL/min
Stirring speed	1500 rpm
Environment	0 to 50°C; max RH 95%
Power supply	220V/50 Hz; 10VA
Dimensions	350 x 310 x 250 mm
Weight	5,5 kg

Mi456 PRO is supplied complete with: Calibration standard TA, Titrant TA, Buffer pH 7.0, Buffer pH 8.2, MA919B/1 pH Electrode, MA831R Temperature probe, MA9011 Refilling Electrolyte Solution 3.5M KCl, for pH electrodes 230 mL bottle, small stir bar, 2 x 50 mL beakers, 2000 µL pipette, test tube set, O-ring, 1 mL syringe, power cable and instruction manual.


Accessories

- MA924B/1** ORP Electrode for Mi455
- MA919B/1** pH Electrode for Mi456
- MA831R** Temperature probe for Mi456
- MA9011** Refilling Electrolyte Solution 3.5M KCl, for ORP electrodes, 230 mL bottle
- Mi0009** Small stir bars (5 pcs)
- Mi0020** 50 mL beaker (4 pcs)
- Mi0021** 25 mL beaker (4 pcs)
- Mi0022** 2000 µL pipette (1 pc)
- Mi0023** Pipette tips for 2000 µL pipette (4 pcs)

Measuring pH in meat

Using MW102 PRO + pH portable meter with a MA920B/1 pH electrode

The pH changes occurring in a carcass during the first 24 hours after slaughter are important for the quality of the final meat or meat products. Protein denaturation will occur if pH falls to too low a level or if a relatively low pH sets in at a time after slaughter where the carcass temperature is still high. This will result in meat with poor water holding capacity and in extreme cases in meat that is PSE.




Calibrate the pH meter using pH 7 and pH 4 standardization buffers.

1. Cut meat sample into small pieces.



2. Weight approximately 10 grams into a blender cup. Run duplicates on each sample.



3. Add 100 ml of distilled deionized water and blend for 30 seconds on high speed.



4. Transfer sample to a beaker. Read the pH as soon as possible.



5. By pressing the HOLD key you can activate the hold function. The measured value is frozen on the display and the "HOLD" tag lights up. Release "HOLD" by pressing HOLD key again.




6. Blender cups, beakers and stir bars can be rinsed in distilled water between samples. The pH electrode should be rinsed with distilled water between each sample and periodically rinsed with acetone from a squeeze bottle to remove fat buildup.















Electrodes & Probes pH, ORP, Conductivity, Dissolved Oxygen



Milwaukee has a wide assortment of pH, ORP, Conductivity and other specialty sensors to meet all your specific requirements.

Finding the right electrode for a specific application is a very important task and in order to solve this selection problem it is important to consider the following: electrode body, reference construction and junction. Below you will find a list of Milwaukee electrodes and probes with corresponding instruments they are supplied with.



OTHER ELECTRODES & PROBES		
	SE220	Double junction pH electrode with 1 meter cable and gel filled electrolyte solution (MW100 / MW101 / MW102)
	SE300	Double junction orp platinum electrode with 1 meter cable and gel filled electrolyte solution (MW500)
	SE510	Conductivity/TDS probe with 1 meter cable (MW301 / MW401)
	SE520	Conductivity/TDS probe with 1 meter cable (MW302 / MW402)
	SE600	Combination probe for pH/EC/TDS with 1 meter cable (MW801 / MW802)
	MA812/2	Conductivity/TDS probe with 2 meter cable (MC310 / MC410)
	MA814DB/1	4-ring Conductivity/TDS/NaCl/Temperature probe with DIN connector and 1 meter cable (MW170)
	MA815D/1	4-ring Conductivity/TDS/NaCl/Temperature probe with DIN connector and 1 meter cable (MW306)
	MA911B/1 MA911B/2	Double junction, gel filled pH electrode with BNC connector, 1 or 2 m cable
	MA906BR/1	pH/Temp amplified probe with 1 meter cable (MW105/MW106)
	MA921B/2	Double junction, gel filled ORP electrode with platinum sensor, BNC connector, 2 m cable
	MA830R	Stainless steel Temperature probe (MW102)
	MA831R	Stainless steel Temperature probe (MW150 / MW151)
	MA840	Polarographic D.O. probe with 4 meter cable (MW600)


Electrode Selection Guide

pH, ORP, Conductivity, Dissolved Oxygen

Milwaukee has a wide assortment of pH, ORP, Conductivity and other specialty sensors to meet all your specific requirements.

Before selecting an electrode, please consult the table below. The recommended electrodes are the ones best suited to each application, however we also ask you to verify the specifications on pages 6-7-8-9

Special electrodes for specific applications can also be manufactured upon request.



Applications	pH	MA905B/3	MA911B/2	SE220	MA913B/3	MA906BR/1	MA916B/1	MA917B/1	MA918B/1	MA919B/1	MA920B/1	MA991B/1	ORP	MA921B/1	SE300	MA923B/3	MA924B/1	MA925B/3	Conductivity	SE510	D.O.	MA840	MA860
Agriculture / Soil testing																							
Aquarium																							
Cheese																							
Dairy products																							
Emulsions																							
Environmental, Pollution																							
Fish farming																							
Food and beverage (general use)																							
Galvanizing waste solution																							
Hi purity water																							
Heavy duty applications																							
In-line applications																							
Laboratory (general use)																							
Meat																							
Paints																							
Paper																							
Photographic chemicals																							
Strong acid																							
Swimming pools																							
Water supply																							
Wine processing																							



Calibration, Maintenance & Cleaning Solutions

Milwaukee offers a wide range of calibration, maintenance & Cleaning solutions.

The use of calibration and cleaning solutions is fundamental for the correct use of electrodes and for obtaining the most accurate and reproducible readings. Often readings are not correct because the sensors have not been properly handled.

Milwaukee standard solutions are available in 230 mL bottles and 20 mL sachets.


Traditional buffer solutions are packed in 230 mL leak-proof bottles and are recommended for lab applications.

Sachets are sealed against light and air and are ideal for on-the-spot calibration.

Simply open, insert the tester or electrode into the sachet and calibrate. Sachets are sold in boxes of 25 pieces.

Calibration, Maintenance & Cleaning Solutions

MA9001	pH 1.68 Calibration Buffer Solution, 230 mL	MA9069	5000 µS/cm Conductivity Calibration Solution, 230 mL
MA9004	pH 4.01 Calibration Buffer Solution, 230 mL	MA9070	Zero Oxygen Solution, 500 mL + 12 g
MA9006	pH 6.86 Calibration Buffer Solution, 230 mL	MA9071	Electrolyte Solution for D.O. Probes, 230 mL
MA9007	pH 7.01 Calibration Buffer Solution, 230 mL	MA9112	pH 12.45 Calibration Buffer Solution, 230 mL
MA9009	pH 9.18 Calibration Buffer Solution, 230 mL	M1000AB	Combination pack of pH buffer solutions, including 10 sachets of M10007 (pH 7.01), 5 sachets of M10000 (rinse), 5 sachets of M10004 (pH 4.01), and 5 sachets of M10010 (pH 10.01); each sachet supplies 20 mL
MA9010	pH 10.01 Calibration Buffer Solution, 230 mL	M10000B	Rinse Solution - Deionized Water (box of 25x20 ml sachet)
MA9011	Refilling Electrolyte Solution 3.5M KCl for pH/ORP electrodes, 230 mL	M10004B	pH 4.01 Calibration Buffer Solution (box of 25x20 ml sachet)
MA9012	Refilling Electrolyte Solution 1M KNO ₃ , 230 mL, food applications	M10007B	pH 7.01 Calibration Buffer Solution (box of 25x20 ml sachet)
MA9015	Storage Solution for pH/ORP electrodes, 230 mL	M10010B	pH 10.01 Calibration Buffer Solution (box of 25x20 ml sachet)
MA9016	Cleaning Solution for pH/ORP electrodes, 230 mL	M10016B	Cleaning Solution for electrodes (box of 25x20 ml sachet)
MA9020	200-275 mV ORP Solution, 230 mL	M10030B	12880 µS/cm Calibration Buffer Solution (box of 25x20 ml sachet)
MA9060	12880 µS/cm Conductivity Calibration Solution, 230 mL	M10031B	1413 µS/cm Calibration Buffer Solution (box of 25x20 ml sachet)
MA9061	1413 µS/cm Conductivity Calibration Solution, 230 mL	M10032B	1382 ppm TDS Calibration Solution (box of 25x20 ml sachet)
MA9062	1382 ppm TDS Calibration Solution, 230 mL	M10038B	6.44 ppt TDS Calibration Solution (box of 25x20 ml sachet)
MA9063	84 µS/cm Conductivity Calibration Solution, 230 mL	M10080B	800 ppm TDS solution (box of 25x20 ml sachet)
MA9064	80000 µS/cm Conductivity Calibration Solution, 230 mL		
MA9065	111.8 mS/cm Conductivity Calibration Solution, 230 mL		
MA9066	100% NaCl Calibration Solution, 230 mL		



pH Electrode Storage and Maintenance

pH Electrode Storage and Maintenance

To ensure a quick response and free-flowing liquid junction, the sensing element and reference junction must not be allowed to dry out. The following instructions apply to refillable electrodes. For gel-filled electrodes, consult instruction manual.

Routine Storage

Soak electrode in a pH Electrode Storage Solution (MA9015). If a storage solution is unavailable, pH 4 buffer or pH7.01 may be used. The fill hole should be covered to prohibit evaporation of reference fill solution.

Maintenance

Cleaning your electrode between and after use will help extend the life of your electrode and avoid the cost of early replacement.

Routine Cleaning

Soak electrode in MA9016 cleaning solution for half an hour, followed by soaking it in storage solution (MA9015) for at least two hours.

Weekly Maintenance

Inspect electrodes for scratches, cracks, salt crystal buildup, or membrane/junction deposits.

Rinse off any salt buildup with distilled water, and remove any membrane/junction deposits as directed in cleaning procedures below. The reference chamber should be drained, flushed with fresh filling solution, and refilled.

WARRANTY POLICY

Milwaukee warrants its instruments to be free of manufacturing defects as follows: bench meters for 3 years, portable and pocket testers for 2 years and electrode/sensors for 6 months (unless otherwise specified).

The warranty period commences from the original date of sale to the user. Warranty is valid only when the product is used under normal conditions and in accordance with the operating limitations and prescribed maintenance procedures.

Milwaukee reserves the right to make improvements in design, construction and appearance of its products without advance notice.

Instrument service

Warranty and non-warranty service are performed by our technicians in Milwaukee headquarters. All items must have a Return Goods Authorization (RGA) number before returning the goods. This number can be obtained by contacting the Milwaukee technical service department at:

tech@milwaukeeinst.com



Bench Meters



Portable Meters



FURTHER INFORMATION

Latest updates on new products, technical tips, download MSDS

Visit our corporate site:

www.milwaukeeinst.com

for the latest updates on new products, technical tips, download of MSDS.

SPECIFIC APPLICATION LITERATURE

Specific application catalogues and leaflets are also available and can be downloaded from our site. Alternatively for a hard copy request please kindly send us an e-mail at:

info@milwaukeeinst.com





milwaukee

Instruments for Water Analysis

Authorized Distributor

www.milwaukeeinstruments.com